

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/PC	0.12	0.25	55	50
SM/APC	0.12	0.25	75	65


A to B

Fibre colour	Side A	Side B
Red	A	B
Green	B	A

Cable description	CFR class	Sheath colour	Sheath Ø [mm]
FO Indoor Uniboot 1x2 G.652.D BLO / J-V(ZN)H	-	Yellow	2.1

Art. No.	Description	Polarity	Length [m]
47338000ZY	PCX - 1LDUP- 1LDUA -01M0-OS2-RDYE	A to B	1.0
47338100ZY	PCX - 1LDUP- 1LDUA -02M0-OS2-RDYE	A to B	2.0
47338200ZY	PCX - 1LDUP- 1LDUA -03M0-OS2-RDYE	A to B	3.0
47338300ZY	PCX - 1LDUP- 1LDUA -04M0-OS2-RDYE	A to B	4.0
47338400ZY	PCX - 1LDUP- 1LDUA -05M0-OS2-RDYE	A to B	5.0
47338500ZY	PCX - 1LDUP- 1LDUA -xxMx-OS2-RDYE	A to B	6.0

Note: Some items in different lengths may not have been included in this table.



Dätwyler IT Infra, itinfra.datwyler.com

DATWYLER

Description

DCS patch cable, LCDU/PC-LCDU/APC, G.652.D BLO, A to B

Drawn	Philipp Bless	01.09.2023	Datwyler description		-			
Checked	André Jaun	05.09.2023	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	08.09.2023	A4	-	According to table	10000288013	01	1 of 1