Cross-section labels:
- 5.0 mm
- 3.0 mm
- 2.0 mm
- Optical fibre, 250 μm
- Semi-tight buffer, 900 μm
- Aramid yarn
- LS0H subunit
- LS0H sheath

Left connectors:
LSH/PC, 0°
Beige housing,
Beige boot

Cable marker
A = white
B = black

Right connectors:
Cable marker
A = white
B = black

LSH/PC, 0°
Beige housing,
Beige boot

100 mm — 100 mm

Length [m]

Art. No.	Description			Polarity	Length [m]
424451	DP1 LSH	-LSH	01M0H-OVOR-OM2	-	1.0
424452	DP1 LSH	-LSH	02M0H-OVOR-OM2	-	2.0
424453	DP1 LSH	-LSH	03M0H-OVOR-OM2	-	3.0
424454	DP1 LSH	-LSH	04M0H-OVOR-OM2	-	4.0
424455	DP1 LSH	-LSH	05M0H-OVOR-OM2	-	5.0
424456	DP1 LSH	-LSH	06M0H-OVOR-OM2	-	6.0
424457	DP1 LSH	-LSH	07M0H-OVOR-OM2	-	7.0
424458	DP1 LSH	-LSH	08M0H-OVOR-OM2	-	8.0
424459	DP1 LSH	-LSH	09M0H-OVOR-OM2	-	9.0
424460	DP1 LSH	-LSH	10M0H-OVOR-OM2	-	10.0
424463	DP1 LSH	-LSH	xxMxH-OVOR-OM2	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	35	30

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G50 OM2 / I-V(ZN)HH	-	Orange	2.0 (3.0 x 5.0)

Description

FO patch cable, LSH/PC, figure 0, OM2

Drawn	Philipp Bless	21.09.2023	Datwyler description	-				
Checked	André Jaun	23.09.2023	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	25.09.2023	A4	-	According to table	10000299014	00	1 of 1