Cross-section dimensions

5.0 mm
3.0 mm
2.0 mm

- Optical fibre, 250 µm
- Semi-tight buffer, 900 µm
- Aramid yarn
- LS0H subunit
- LS0H sheath

Left connector
ST/PC, 0° Cable marker
Metal housing, A = white
Black boot B = black

Right connector
Cable marker ST/PC, 0°
A = white Metal housing,
B = black Black boot

100 mm

Length [m]

A

B

Art. No.	Description			Polarity	Length [m]
422231	DPX ST	-ST	01M0H-OVTK-OM3	-	1.0
422232	DPX ST	-ST	02M0H-OVTK-OM3	-	2.0
422233	DPX ST	-ST	03M0H-OVTK-OM3	-	3.0
422234	DPX ST	-ST	04M0H-OVTK-OM3	-	4.0
422235	DPX ST	-ST	05M0H-OVTK-OM3	-	5.0
422236	DPX ST	-ST	06M0H-OVTK-OM3	-	6.0
422237	DPX ST	-ST	07M0H-OVTK-OM3	-	7.0
422238	DPX ST	-ST	08M0H-OVTK-OM3	-	8.0
422239	DPX ST	-ST	09M0H-OVTK-OM3	-	9.0
422240	DPX ST	-ST	10M0H-OVTK-OM3	-	10.0
422243	DPX ST	-ST	xxMxH-OVTK-OM3	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	35	30

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G50 OM3 / I-V(ZN)HH	-	Turquoise	2.0 (3.0 x 5.0)

Dätwyler IT Infra, itinfra.datwyler.com

DATWYLER

Description

FO patch cable, ST/PC, figure 0, OM3

			Datwyler description	-					
Drawn	Philipp Bless	21.09.2023							
Checked	André Jaun	23.09.2023	Size	Scale	Article number	Drawing number	Revision	Page	
Approved	Kai Wirkus	25.09.2023	A4	-	According to table	10000299037	00	1 of 1	