| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |

5.0 mm

3.0 mm
2.0 mm

Optical fibre, 250 µm
Semi-tight buffer, 900 µm
Aramid yarn
LS0H subunit
LS0H sheath

LCD/PC, 0°
Blue housing,
Blue boot

Cable marker
A = white
B = black

Cable marker
A = white
B = black

LCD/APC, 8°
Green housing,
Green boot

100 mm

100 mm

Length [m]

A to B

Fibre colour	Side A	Side B
Red	A	B
Green	B	A

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/PC	0.12	0.25	55	50
SM/APC	0.12	0.25	70	65

Art. No.	Description	Polarity	Length [m]
423911	DAX LCD/PC -LCD/APC01M0H-OVGE-OS2	A to B	1.0
423912	DAX LCD/PC -LCD/APC02M0H-OVGE-OS2	A to B	2.0
423913	DAX LCD/PC -LCD/APC03M0H-OVGE-OS2	A to B	3.0
423914	DAX LCD/PC -LCD/APC04M0H-OVGE-OS2	A to B	4.0
423915	DAX LCD/PC -LCD/APC05M0H-OVGE-OS2	A to B	5.0
423916	DAX LCD/PC -LCD/APC06M0H-OVGE-OS2	A to B	6.0
423917	DAX LCD/PC -LCD/APC07M0H-OVGE-OS2	A to B	7.0
423918	DAX LCD/PC -LCD/APC08M0H-OVGE-OS2	A to B	8.0
423919	DAX LCD/PC -LCD/APC09M0H-OVGE-OS2	A to B	9.0
423920	DAX LCD/PC -LCD/APC10M0H-OVGE-OS2	A to B	10.0
423923	DAX LCD/PC -LCD/APCxxMxH-OVGE-OS2	A to B	xx.x

Note: Some items in different lengths may not have been included in this table.

Cable description		CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH		-	Yellow	2.0 (3.0 x 5.0)

Dätwyler IT Infra, itinfra.datwyler.com

DÄTWYLER

Description

FO patch cable, LCD/PC-LCD/APC, figure 0, G.652.D BLO, A to B

			Datwyler description	-				
Drawn	Philipp Bless	21.09.2023						
Checked	André Jaun	23.09.2023	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	25.09.2023	A4	-	According to table	10000299049	00	1 of 1