5.0 mm

3.0 mm
2.0 mm

- Optical fibre, 250 µm
- Semi-tight buffer, 900 µm
- Aramid yarn
- LS0H subunit
- LS0H sheath

LSH/PC, 0°
Blue housing,
Blue boot

Cable marker
A = white
B = black

Cable marker
A = white
B = black

LSH/PC, 0°
Blue housing,
Blue boot

A

B

100 mm

A

B

100 mm

Length [m]

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/PC	0.12	0.25	55	50

Art. No.	Description			Polarity	Length [m]
424411	DPX LSH	-LSH	01M0H-OVYE-OS2	-	1.0
424412	DPX LSH	-LSH	02M0H-OVYE-OS2	-	2.0
424413	DPX LSH	-LSH	03M0H-OVYE-OS2	-	3.0
424414	DPX LSH	-LSH	04M0H-OVYE-OS2	-	4.0
424415	DPX LSH	-LSH	05M0H-OVYE-OS2	-	5.0
424416	DPX LSH	-LSH	06M0H-OVYE-OS2	-	6.0
424417	DPX LSH	-LSH	07M0H-OVYE-OS2	-	7.0
424418	DPX LSH	-LSH	08M0H-OVYE-OS2	-	8.0
424419	DPX LSH	-LSH	09M0H-OVYE-OS2	-	9.0
424420	DPX LSH	-LSH	10M0H-OVYE-OS2	-	10.0
424423	DPX LSH	-LSH	xxMxH-OVGE-OS2	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Cable description		CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH		-	Yellow	2.0 (3.0 x 5.0)

Dätwyler IT Infra, itinfra.datwyler.com

DATWYLER

Description

FO patch cable, LSH/PC, figure 0, G.652.D BLO

Drawn	Philipp Bless	21.09.2023	Datwyler description	-				
Checked	André Jaun	23.09.2023	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	25.09.2023	A4	-	According to table	10000299060	00	1 of 1