5.0 mm

3.0 mm
2.0 mm

Optical fibre, 250 µm
Semi-tight buffer, 900 µm
Aramid yarn
LS0H subunit
LS0H sheath

SCD/PC, 0°
Blue housing,
Blue boot

Cable marker
A = white
B = black

Cable marker
A = white
B = black

SCD/APC, 8°
Green housing,
Green boot

100 mm

100 mm

Length [m]

A to B

Fibre colour	Side A	Side B
Red	A	B
Green	B	A

Art. No.	Description	Polarity	Length [m]
421711	DAX SCD/PC -SCD/APC01M0H-OVGE-OS2	A to B	1.0
421712	DAX SCD/PC -SCD/APC02M0H-OVGE-OS2	A to B	2.0
421713	DAX SCD/PC -SCD/APC03M0H-OVGE-OS2	A to B	3.0
421714	DAX SCD/PC -SCD/APC04M0H-OVGE-OS2	A to B	4.0
421715	DAX SCD/PC -SCD/APC05M0H-OVGE-OS2	A to B	5.0
421716	DAX SCD/PC -SCD/APC06M0H-OVGE-OS2	A to B	6.0
421717	DAX SCD/PC -SCD/APC07M0H-OVGE-OS2	A to B	7.0
421718	DAX SCD/PC -SCD/APC08M0H-OVGE-OS2	A to B	8.0
421719	DAX SCD/PC -SCD/APC09M0H-OVGE-OS2	A to B	9.0
421720	DAX SCD/PC -SCD/APC10M0H-OVGE-OS2	A to B	10.0
421723	DAX SCD/PC -SCD/APCxxMxH-OVGE-OS2	A to B	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/PC	0.12	0.25	55	50
SM/APC	0.12	0.25	70	65

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH	-	Yellow	2.0 (3.0 x 5.0)

Dätwyler IT Infra, itinfra.datwyler.com

DÄTWYLER

Description

FO patch cable, SCD/PC-SCD/APC, figure 0, G.652.D BLO, A to B

Datwyler description -

Drawn	Philipp Bless	21.09.2023						
Checked	André Jaun	23.09.2023	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	25.09.2023	A4	-	According to table	10000299069	00	1 of 1