



ST/PC, 0° Cable marker
Metal housing, A = white
Black boot B = black

Cable marker FC/PC, 0°
A = white Metal housing,
B = black Black boot

Art. No.	Description	Polarity	Length [m]
422511	DA1 ST -FC 01M0H-OVGE-OS2	-	1.0
422512	DA1 ST -FC 02M0H-OVGE-OS2	-	2.0
422513	DA1 ST -FC 03M0H-OVGE-OS2	-	3.0
422514	DA1 ST -FC 04M0H-OVGE-OS2	-	4.0
422515	DA1 ST -FC 05M0H-OVGE-OS2	-	5.0
422516	DA1 ST -FC 06M0H-OVGE-OS2	-	6.0
422517	DA1 ST -FC 07M0H-OVGE-OS2	-	7.0
422518	DA1 ST -FC 08M0H-OVGE-OS2	-	8.0
422519	DA1 ST -FC 09M0H-OVGE-OS2	-	9.0
422520	DA1 ST -FC 10M0H-OVGE-OS2	-	10.0
422523	DA1 ST -FC xxMxH-OVGE-OS2	-	xx.X

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/PC	0.12	0.25	55	50

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH	-	Yellow	2.0 (3.0 x 5.0)

 Datwyler IT Infra, itinfra.datwyler.com DATWYLER			Description FO patch cable, ST/PC-FC/PC, figure 0, G.652.D BLO					
Drawn	Philipp Bless	21.09.2023	Datwyler description		-			
Checked	André Jaun	23.09.2023	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	25.09.2023	A4	-	According to table	10000299073	00	1 of 1