5.2 mm

3.2 mm
2.0 mm

Optical fibre, 250 µm
Tight buffer, 900 µm
Aramid yarn
LS0H subunit
LS0H sheath

LCD/PC, 0°
Beige housing,
Beige boot

Cable marker
A = white
B = black

Cable marker
A = white
B = black

SCD/PC, 0°
Beige housing,
Beige boot

A

B

A

B

100 mm

100 mm

Length [m]

A to B

Fibre colour	Side A	Side B
Red	A	B
Green	B	A

Art. No.	Description	Polarity	Length [m]
43134100BY	DAX LCD/PC -SCD/PC 01M0HBOVVI-OM4	A to B	1.0
43134200BY	DAX LCD/PC -SCD/PC 02M0HBOVVI-OM4	A to B	2.0
43134300BY	DAX LCD/PC -SCD/PC 03M0HBOVVI-OM4	A to B	3.0
43134400BY	DAX LCD/PC -SCD/PC 04M0HBOVVI-OM4	A to B	4.0
43134500BY	DAX LCD/PC -SCD/PC 05M0HBOVVI-OM4	A to B	5.0
43134600BY	DAX LCD/PC -SCD/PC 06M0HBOVVI-OM4	A to B	6.0
43134700BY	DAX LCD/PC -SCD/PC 07M0HBOVVI-OM4	A to B	7.0
43134800BY	DAX LCD/PC -SCD/PC 08M0HBOVVI-OM4	A to B	8.0
43134900BY	DAX LCD/PC -SCD/PC 09M0HBOVVI-OM4	A to B	9.0
43135000BY	DAX LCD/PC -SCD/PC 10M0HBOVVI-OM4	A to B	10.0
43135100BY	DAX LCD/PC -SCD/PC xxMxHBOVVI-OM4	A to B	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	35	30

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G50 OM4 / I-V(ZN)HH	B2ca-s1a,d0,a1	Heather violet	2.0 (3.2 x 5.2)

Dätwyler IT Infra, itinfra.datwyler.com

DÄTWYLER

Description

FO patch cable, LCD/PC-SCD/PC, figure 0, OM4, A to B, B2ca

Drawn	Philipp Bless	25.06.2024	Datwyler description	-				
Checked	André Jaun	26.06.2024	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	28.06.2024	A4	-	According to table	10000327037	00	1 of 1