Cross-section dimensions:
- 5.2 mm (width)
- 3.2 mm
- 2.0 mm

Callouts:
- Optical fibre, 250 µm
- Tight buffer, 900 µm
- Aramid yarn
- LS0H subunit
- LS0H sheath

Left connector:
LCD/PC, 0°
Beige housing,
Beige boot

Cable marker
A = white
B = black

Right connector:
Cable marker
A = white
B = black

ST/PC, 0°
Metal housing,
Black boot

100 mm — Length [m] — 100 mm

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	35	30

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G50 OM4 / I-V(ZN)HH	B2ca-s1a,d0,a1	Heather violet	2.0 (3.2 x 5.2)

Art. No.	Description	Polarity	Length [m]
42230100BY	DA LCD/PC -ST/PC 01M0HBOVVI-OM4	-	1.0
42230200BY	DA LCD/PC -ST/PC 02M0HBOVVI-OM4	-	2.0
42230300BY	DA LCD/PC -ST/PC 03M0HBOVVI-OM4	-	3.0
42230400BY	DA LCD/PC -ST/PC 04M0HBOVVI-OM4	-	4.0
42230500BY	DA LCD/PC -ST/PC 05M0HBOVVI-OM4	-	5.0
42230600BY	DA LCD/PC -ST/PC 06M0HBOVVI-OM4	-	6.0
42230700BY	DA LCD/PC -ST/PC 07M0HBOVVI-OM4	-	7.0
42230800BY	DA LCD/PC -ST/PC 08M0HBOVVI-OM4	-	8.0
42230900BY	DA LCD/PC -ST/PC 09M0HBOVVI-OM4	-	9.0
42231000BY	DA LCD/PC -ST/PC 10M0HBOVVI-OM4	-	10.0
50361700BY	DA LCD/PC -ST/PC xxMxHBOVVI-OM4	-	xx.x

Note: Some items in different lengths may not have been included in this table.

DATWYLER

Dätwyler IT Infra, itinfra.datwyler.com

Description

FO patch cable, LCD/PC-ST/PC, figure 0, OM4, B2ca

			Datwyler description	-
Drawn	Philipp Bless	25.06.2024		
Checked	André Jaun	26.06.2024		
Approved	Kai Wirkus	28.06.2024		

Size	Scale	Article number	Drawing number	Revision	Page
A4	-	According to table	10000327038	00	1 of 1