



LCD/APC, 8°
Green housing,
Green boot

Cable marker
A = white
B = black

Cable marker
A = white
B = black

SCD/PC, 0°
Blue housing,
Blue boot

A to B

Fibre colour	Side A	Side B
Red	A	B
Green	B	A

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/APC	0.12	0.25	70	65
SM/PC	0.12	0.25	55	50

Art. No.	Description	Polarity	Length [m]
42191100BY	DAX LCD/APC-SCD/PC 01M0HBOV/GE-OS2	A to B	1.0
42191200BY	DAX LCD/APC-SCD/PC 02M0HBOV/GE-OS2	A to B	2.0
42191300BY	DAX LCD/APC-SCD/PC 03M0HBOV/GE-OS2	A to B	3.0
42191400BY	DAX LCD/APC-SCD/PC 04M0HBOV/GE-OS2	A to B	4.0
42191500BY	DAX LCD/APC-SCD/PC 05M0HBOV/GE-OS2	A to B	5.0
42191600BY	DAX LCD/APC-SCD/PC 06M0HBOV/GE-OS2	A to B	6.0
42191700BY	DAX LCD/APC-SCD/PC 07M0HBOV/GE-OS2	A to B	7.0
42191800BY	DAX LCD/APC-SCD/PC 08M0HBOV/GE-OS2	A to B	8.0
42191900BY	DAX LCD/APC-SCD/PC 09M0HBOV/GE-OS2	A to B	9.0
42192000BY	DAX LCD/APC-SCD/PC 10M0HBOV/GE-OS2	A to B	10.0
42192300BY	DAX LCD/APC-SCD/PC xxMxHBOV/GE-OS2	A to B	xx.x

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH	B2ca-s1a,d0,a1	Yellow	2.0 (3.2 x 5.2)

 DATWYLER		Dätwyler IT Infra, itinfra.datwyler.com		Description				
		FO patch cable, LCD/APC-SCD/PC, figure 0, G.652.D BLO, A to B, B2ca				Datwyler description		-
Drawn	Philipp Bless	25.06.2024	Size	Scale	Article number	Drawing number	Revision	Page
Checked	André Jaun	26.06.2024	A4	-	According to table	10000327047	00	1 of 1
Approved	Kai Wirkus	28.06.2024						

Note: Some items in different lengths may not have been included in this table.