FO patch cable, LSH/APC, figure 0, G.652.D BLO, B2ca

Cross-section dimensions: 5.2 mm, 3.2 mm, 2.0 mm

- Optical fibre, 250 µm
- Tight buffer, 900 µm
- Aramid yarn
- LS0H subunit
- LS0H sheath

LSH/APC, 8°
Green housing,
Green boot

Cable marker
A = white
B = black

100 mm

Length [m]

Art. No.	Description	Polarity	Length [m]
42881100BY	DP LSH/APC-LSH/APC01M0HBOVGE-OS2	-	1.0
42881200BY	DP LSH/APC-LSH/APC02M0HBOVGE-OS2	-	2.0
42881300BY	DP LSH/APC-LSH/APC03M0HBOVGE-OS2	-	3.0
42881400BY	DP LSH/APC-LSH/APC04M0HBOVGE-OS2	-	4.0
42881500BY	DP LSH/APC-LSH/APC05M0HBOVGE-OS2	-	5.0
42881600BY	DP LSH/APC-LSH/APC06M0HBOVGE-OS2	-	6.0
42881700BY	DP LSH/APC-LSH/APC07M0HBOVGE-OS2	-	7.0
42881800BY	DP LSH/APC-LSH/APC08M0HBOVGE-OS2	-	8.0
42881900BY	DP LSH/APC-LSH/APC09M0HBOVGE-OS2	-	9.0
42882000BY	DP LSH/APC-LSH/APC10M0HBOVGE-OS2	-	10.0
42882300BY	DP LSH/APC-LSH/APCxxMxHBOVGE-OS2	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/APC	0.12	0.25	70	65

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH	B2ca-s1a,d0,a1	Yellow	2.0 (3.2 x 5.2)