



Art. No.	Description	Polarity	Length [m]
42181100BY	DA LSH/APC-SCD/PC 01M0HBOVGE-OS2	-	1.0
42181200BY	DA LSH/APC-SCD/PC 02M0HBOVGE-OS2	-	2.0
42181300BY	DA LSH/APC-SCD/PC 03M0HBOVGE-OS2	-	3.0
42181400BY	DA LSH/APC-SCD/PC 04M0HBOVGE-OS2	-	4.0
42181500BY	DA LSH/APC-SCD/PC 05M0HBOVGE-OS2	-	5.0
42181600BY	DA LSH/APC-SCD/PC 06M0HBOVGE-OS2	-	6.0
42181700BY	DA LSH/APC-SCD/PC 07M0HBOVGE-OS2	-	7.0
42181800BY	DA LSH/APC-SCD/PC 08M0HBOVGE-OS2	-	8.0
42181900BY	DA LSH/APC-SCD/PC 09M0HBOVGE-OS2	-	9.0
42182000BY	DA LSH/APC-SCD/PC 10M0HBOVGE-OS2	-	10.0
50365600BY	DA LSH/APC-SCD/PC xxMxHBOVGE-OS2	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/APC	0.12	0.25	70	65
SM/PC	0.12	0.25	55	50

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor Duplex G.652.D BLO / I-V(ZN)HH	B2ca-s1a,d0,a1	Yellow	2.0 (3.2 x 5.2)

 DATWYLER		Dätwyler IT Infra, itinfra.datwyler.com		Description				
				FO patch cable, LSH/APC-SCD/PC, figure 0, G.652.D BLO, B2ca				
Drawn	Philipp Bless	25.06.2024	Datwyler description		-			
Checked	André Jaun	26.06.2024	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	28.06.2024	A4	-	According to table	10000327058	00	1 of 1