Cross-section labels:
- 4.1 mm
- 2.0 mm
- Optical fibre, 250 µm
- Tight buffer, 900 µm
- Aramid yarn
- LS0H sheath

Left connector:
- LCD/PC, 0°
- Beige housing, Beige boot
- Cable marker
- A = white
- B = black

Right connector:
- Cable marker
- A = white
- B = black
- LCD/PC, 0°
- Beige housing, Beige boot

- 100 mm
- 100 mm
- Length [m]

A to B

Fibre colour	Side A	Side B
Red	A	B
Green	B	A

Art. No.	Description	Polarity	Length [m]
42333108BY	DPX LCD/PC -LCD/PC 01M0HBZCTK-OM3	A to B	1.0
42333208BY	DPX LCD/PC -LCD/PC 02M0HBZCTK-OM3	A to B	2.0
42333308BY	DPX LCD/PC -LCD/PC 03M0HBZCTK-OM3	A to B	3.0
42333408BY	DPX LCD/PC -LCD/PC 04M0HBZCTK-OM3	A to B	4.0
42333508BY	DPX LCD/PC -LCD/PC 05M0HBZCTK-OM3	A to B	5.0
42333608BY	DPX LCD/PC -LCD/PC 06M0HBZCTK-OM3	A to B	6.0
42333708BY	DPX LCD/PC -LCD/PC 07M0HBZCTK-OM3	A to B	7.0
42333808BY	DPX LCD/PC -LCD/PC 08M0HBZCTK-OM3	A to B	8.0
42333908BY	DPX LCD/PC -LCD/PC 09M0HBZCTK-OM3	A to B	9.0
42334008BY	DPX LCD/PC -LCD/PC 10M0HBZCTK-OM3	A to B	10.0
42334308BY	DPX LCD/PC -LCD/PC xxMxHBZCTK-OM3	A to B	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	35	30

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor ZipCord G50 OM3 / I-V(ZN)H	B2ca-s2,d0,a1	Turquoise	2.0 (2.0 x 4.1)

DÄTWYLER

Dätwyler IT Infra, itinfra.datwyler.com

Description

FO patch cable, LCD/PC, figure 8, OM3, A to B, B2ca

Drawn	Philipp Bless	25.06.2024	Datwyler description	-			
Checked	André Jaun	26.06.2024	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	28.06.2024	A4	-	According to table	10000327067	00	1 of 1