Cross-section labels:
- 4.1 mm (width)
- 2.0 mm (height)
- Optical fibre, 250 µm
- Tight buffer, 900 µm
- Aramid yarn
- LS0H sheath

Left side:
- LSH/PC, 0° Beige housing, Beige boot
- Cable marker A = white, B = black
- A
- B
- 100 mm

Right side:
- Cable marker A = white, B = black
- LSH/PC, 0° Beige housing, Beige boot
- A
- B
- 100 mm

Length [m]

Art. No.	Description	Polarity	Length [m]
50355708BY	DP LSH/PC -LSH/PC 01M0HBZCTK-OM3	-	1.0
50355808BY	DP LSH/PC -LSH/PC 02M0HBZCTK-OM3	-	2.0
50355908BY	DP LSH/PC -LSH/PC 03M0HBZCTK-OM3	-	3.0
50356008BY	DP LSH/PC -LSH/PC 04M0HBZCTK-OM3	-	4.0
50356108BY	DP LSH/PC -LSH/PC 05M0HBZCTK-OM3	-	5.0
50356208BY	DP LSH/PC -LSH/PC 06M0HBZCTK-OM3	-	6.0
50356308BY	DP LSH/PC -LSH/PC 07M0HBZCTK-OM3	-	7.0
50356408BY	DP LSH/PC -LSH/PC 08M0HBZCTK-OM3	-	8.0
50356508BY	DP LSH/PC -LSH/PC 09M0HBZCTK-OM3	-	9.0
50356608BY	DP LSH/PC -LSH/PC 10M0HBZCTK-OM3	-	10.0
50356708BY	DP LSH/PC -LSH/PC xxMxHBZCTK-OM3	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	35	30

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor ZipCord G50 OM3 / I-V(ZN)H	B2ca-s2,d0,a1	Turquoise	2.0 (2.0 x 4.1)

Description

FO patch cable, LSH/PC, figure 8, OM3, B2ca

Drawn	Philipp Bless	25.06.2024	Datwyler description -
Checked	André Jaun	26.06.2024	
Approved	Kai Wirkus	28.06.2024	

Size	Scale	Article number	Drawing number	Revision	Page
A4	-	According to table	10000327071	00	1 of 1