



Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/APC	0.12	0.25	70	65
SM/PC	0.12	0.25	55	50

Art. No.	Description	Polarity	Length [m]
50351508BY	DA LCD/APC-ST/PC 01M0HBZCGE-OS2	-	1.0
50351608BY	DA LCD/APC-ST/PC 02M0HBZCGE-OS2	-	2.0
50351708BY	DA LCD/APC-ST/PC 03M0HBZCGE-OS2	-	3.0
50351808BY	DA LCD/APC-ST/PC 04M0HBZCGE-OS2	-	4.0
50351908BY	DA LCD/APC-ST/PC 05M0HBZCGE-OS2	-	5.0
50352008BY	DA LCD/APC-ST/PC 06M0HBZCGE-OS2	-	6.0
50352108BY	DA LCD/APC-ST/PC 07M0HBZCGE-OS2	-	7.0
50352208BY	DA LCD/APC-ST/PC 08M0HBZCGE-OS2	-	8.0
50352308BY	DA LCD/APC-ST/PC 09M0HBZCGE-OS2	-	9.0
50352408BY	DA LCD/APC-ST/PC 10M0HBZCGE-OS2	-	10.0
50352508BY	DA LCD/APC-ST/PC xxMxHBZCGE-OS2	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor ZipCord G.652.D BLO / I-V(ZN)H	B2ca-s2,d0,a1	Yellow	2.0 (2.0 x 4.1)

Dätwyler IT Infra, itinfra.datwyler.com

DATWYLER

Description

FO patch cable, LCD/APC-ST/PC, figure 8, G.652.D BLO, B2ca

Drawn	Philipp Bless	25.06.2024	Datwyler description		-			
Checked	André Jaun	26.06.2024	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	28.06.2024	A4	-	According to table	10000327088	00	1 of 1