



ST/PC, 0° Cable marker
Metal housing, A = white
Black boot B = black

Cable marker ST/PC, 0°
A = white Metal housing,
B = black Black boot

Art. No.	Description	Polarity	Length [m]
42221108BY	DP ST/PC -ST/PC 01M0HBZCGE-OS2	-	1.0
42221208BY	DP ST/PC -ST/PC 02M0HBZCGE-OS2	-	2.0
42221308BY	DP ST/PC -ST/PC 03M0HBZCGE-OS2	-	3.0
42221408BY	DP ST/PC -ST/PC 04M0HBZCGE-OS2	-	4.0
42221508BY	DP ST/PC -ST/PC 05M0HBZCGE-OS2	-	5.0
42221608BY	DP ST/PC -ST/PC 06M0HBZCGE-OS2	-	6.0
42221708BY	DP ST/PC -ST/PC 07M0HBZCGE-OS2	-	7.0
42221808BY	DP ST/PC -ST/PC 08M0HBZCGE-OS2	-	8.0
42221908BY	DP ST/PC -ST/PC 09M0HBZCGE-OS2	-	9.0
50353208BY	DP ST/PC -ST/PC 10M0HBZCGE-OS2	-	10.0
50354408BY	DP ST/PC -ST/PC xxMxHBZCGE-OS2	-	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/PC	0.12	0.25	55	50

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor ZipCord G.652.D BLO / I-V(ZN)H	B2ca-s2,d0,a1	Yellow	2.0 (2.0 x 4.1)

 Dätwyler IT Infra, itinfra.datwyler.com DATWYLER			Description FO patch cable, ST/PC, figure 8, G.652.D BLO, B2ca					
Drawn	Philipp Bless	25.06.2024	Datwyler description		-			
Checked	André Jaun	26.06.2024	Size	Scale	Article number	Drawing number	Revision	Page
Approved	Kai Wirkus	28.06.2024	A4	-	According to table	10000327106	00	1 of 1