

CU 6002 4P

Data cable, U/FTP, Category 6, AWG23, Euroclass Cca

300 MHz



- 1 Inner conductor: AWG23 Bare copper wire
- 2 PE insulated conductor: 1.3 mm Ø
- 3 Screen (pair): Alu PETP foil
- 4 Drain wire: Tinned copper wire
- 5 Outer sheath: FRNC/LS0H orange RAL 2003



Descrizione

Electrically and mechanically advanced quality Cat.6 data cable - fulfils the requirements of ISO/IEC 11801, IEC 61156-5, EN 50173-1 and EN 50288-5-1.

Good shielding effect due to individually screened pairs.

Compatible with all current connecting hardware in accordance with EN 50173 and ISO/IEC 11801.

Applicazione

Data cable for structured premises cabling.

For the transmission of digital and analogue voice, video and data signals.

Suitable for all ICT network applications up to class E applications (250 MHz) in accordance with EN 50173-1 and ISO/IEC 11801.

Applicable for Power over Ethernet (PoE) / PoE+.

Costruzione

Materiale della guaina esterna	FRNC/LSZH
Colore della guaina esterna	arancia

Proprietà generali

Installation temperature	0 °C - +50 °C
Operating temperature	-20 °C - +60 °C
Colore del filo	bianco/blu, bianco/arancio, bianco/verde, bianco/marrone, in conformità alle norme IEC 60189 e IEC 60708
Impronta	DATWYLER «cable type» «additional text» «batch number» «meter marks»
Campo di applicazione	Interno

Proprietà elettriche

Categoria	Cat.6
Gbit/s	A 1 Gbit/s
Loop resistance at 20 °C	150 Ω/km
Operating capacity	42 pF/m
Impedenza a 100 MHz, ±5Ω	100 Ω
NVP %	79
Ritardo Skew	5 ns/100 m
Schermatura	schermati
Near end unbalance attenuation LCL at 1-600 MHz	40 dB
Transfer impedance 1/10/30 MHz	< 50/100/200 mΩ/m
Attenuazione di accoppiamento	55 dB
Segregation class	c

Frequenza [MHz]	Categoria	Attenuazione [dB]	NEXT [dB]	PS-NEXT [dB]	ACR-N [dB]	PS-ACR-N [dB]	ACR-F [dB]	Perdita di ritorno [dB]
1		2,1	93	90	91	88	96	26
4		3,8	93	90	89	86	96	28
10		5,9	93	90	87	84	96	30
100	5e	19,8	93	90	73	70	74	30
250	6	30	83	80	53	50	56	27
300		32	79	76	48	44	49	24

I dati sulle prestazioni indicati sono valori tipici misurati.

Proprietà meccaniche

Solid / Flex	stabile
AWG	23
Raggio di curvatura minimo (installato in modo permanente)	28 mm
Curvatura minima (durante l'installazione)	56 mm
Minimum number of impacts	10

Standards

Reaction to fire	EN 13501-6
Euroclass	C _{ca}
Densità del fumo	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2, AREI-RGIE Section 4.3.3 SD
Zero alogeni nessun gas corrosivo	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2, AREI-RGIE Section 4.3.3 SA
Propagazione della fiamma	AREI-RGIE Section 4.3.3 F1, EN 60332-1-2, IEC 60332-1-2, VDE 0482-332-1-2
Standard dei cavi	ISO/IEC 61156-5, EN 50288-5-1
Cat./Class	Cat.6 / Class E
PoE	IEEE 802.3bt Type 4 (100W)

Versioni

Codice art.	Prodotto	Reaction to fire	Dimensions n x p x [mm (AWG)]	Dimensioni della guaina esterna [mm]	Tasso di CU [kg/km]	Weight [kg/km]	Fire load [kWh/m]	Unità di imballaggio	GTIN / EAN
18293600CK	CU 6002 4P	Cca-s1a,d1,a1	4 x 2 x 0.55 (AWG23)	6.8	20,0	46,6	0,15	1000 m tamburo	40393910040227
18293600CL	CU 6002 4P	Cca-s1a,d1,a1	4 x 2 x 0.55 (AWG23)	6.8	20,0	46,6	0,15	500 m tamburo	40393910040210

