

CU 6552 4P / 2x4P F8

Data cable, F/FTP, Category 6_A, AWG 23, Euroclass Dca
500 MHz



- 1 Inner conductor: AWG23 Bare copper wire
- 2 PE insulated conductor: 1.3 mm Ø
- 3 Screen (pair): Alu PETP foil
- 4 Drain wire: Tinned copper wire
- 5 Overall screen: Alu PETP foil
- 6 Outer sheath: FRNC/LS0H orange RAL 2003



Descrizione

Electrically and mechanically improved quality Cat.6A data cable - fulfils the requirements of ISO/IEC 11801, IEC 61156-5, EN 50173-1 and prEN 50288-10-1.

Excellent shielding effect due to individually screened pairs and overall foil screen.

Compatible with all current connecting hardware in accordance with EN 50173 and ISO/IEC 11801.

Applicazione

Data cable for structured premises cabling.

For the transmission of digital and analogue voice, video and data signals.

Suitable for all ICT network applications up to class EA applications (500 MHz) in accordance with EN 50173-1 and ISO/IEC 11801.

Applicable for Power over Ethernet (PoE) / PoE+.

Supported Applications: 10Base-T, 100Base-T, 1000Base-T, 2.5GBase-T, 5GBase-T, 10GBase-T, Fieldbus

Costruzione

Materiale della guaina esterna	FRNC/LSZH
Colore della guaina esterna	arancia

Proprietà generali

Installation temperature	0 °C - +50 °C
Operating temperature	-20 °C - +60 °C
Colore del filo	bianco/blu, bianco/arancio, bianco/verde, bianco/marrone, in conformità alle norme IEC 60189 e IEC 60708
Impronta	DATWYLER «cable type» «additional text» «batch number» «meter marks»
Campo di applicazione	Interno

Proprietà elettriche

Categoria	Cat.6 _A
Gbit/s	A 10 Gbit/s
Loop resistance at 20 °C	150 Ω/km
Operating capacity	42 pF/m
Impedenza a 100 MHz, ±5Ω	100 Ω
NVP %	79
Ritardo Skew	5 ns/100 m
Schermatura	schermati
Near end unbalance attenuation LCL at 1-600 MHz	40 dB
Transfer impedance 1/10/30 MHz	< 50/100/200 mΩ/m
Attenuazione di accoppiamento	70 dB
Segregation class	c

Frequenza [MHz]	Categoria	Attenuazione [dB]	NEXT [dB]	PS-NEXT [dB]	ACR-N [dB]	PS-ACR-N [dB]	ACR-F [dB]	Perdita di ritorno [dB]
1		2,1	93	90	91	88	96	26
4		3,8	93	90	89	86	96	28
10		5,9	93	90	87	84	96	30
100	5e	19	93	90	73	70	74	30
250	6	30	83	80	53	50	56	27
500	6 _A	43	75	72	32	29	33	21

I dati sulle prestazioni indicati sono valori tipici misurati.

Proprietà meccaniche

Solid / Flex	stabile
AWG	23
Raggio di curvatura minimo (installato in modo permanente)	28 mm
Curvatura minima (durante l'installazione)	56 mm
Minimum number of impacts	10
Resistenza alla trazione (2x4P)	190 N

Standards

Reaction to fire	EN 13501-6
Euroclass	D _{ca}
Densità del fumo	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2, AREI-RGIE Section 4.3.3 SD
Zero alogeni nessun gas corrosivo	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2, AREI-RGIE Section 4.3.3 SA
Propagazione della fiamma	AREI-RGIE Section 4.3.3 F1, EN 60332-1-2, IEC 60332-1-2, VDE 0482-332-1-2
Flame spread	IEC 60332-3-24, EN 60332-3-24, AREI-RGIE Section 4.3.3 F2
Standard dei cavi	ISO/IEC 61156-5, EN 50288-10-1
Cat./Class	Cat.6 _A / Class E _A
PoE	IEEE 802.3bt Type 4 (100W)

Versioni

Codice art.	Prodotto	Reaction to fire	Dimensions n x p x [mm (AWG)]	Dimensioni della guaina esterna [mm]	Tasso di CU [kg/km]	Weight [kg/km]	Fire load [kWh/m]	Unità di imballaggio	GTIN / EAN
19145400DK	CU 6552 4P	Dca-s2,d1,a1	4 x 2 x 0.55 (AWG23)	7	20,0	48,4	0,14	1000 m tamburo	40393910030815
19145400DL	CU 6552 4P	Dca-s2,d1,a1	4 x 2 x 0.55 (AWG23)	7	20,0	48,4	0,14	500 m tamburo	40393910030808
19145600DL	CU 6552 2x4P	Dca-s2,d1,a1	2 x (4 x 2 x 0.55 (AWG23))	7.0 x 14.3	40,0	101,4	0,28	500 m tamburo	40393910030655

Con riserva di modifiche tecniche

A partire da 2024-02-16 16:48:01