

## CU 7702 4P flex TC

Flexible data cable, S/FTP, Category 7, AWG26, Euroclass C<sub>ca</sub>

862 MHz



- 1 Inner conductor: AWG26, tinned copper wire, stranded
- 2 PE insulated conductor: Ø 1.02 mm
- 3 Screen (pair): Alu PETP foil
- 4 Overall screen: tinned braided copper
- 5 Outer sheath: FRNC/LSZH, various colours



### Description

Electrically and mechanically superior quality Cat.7 patch cord - exceeds the requirements of ISO/IEC 11801, IEC 61156-6, EN 50173-1 and EN 50288-4-2.

Excellent shielding effect due to individually screened pairs and overall copper braid.

Easy wire identification and termination due to different coloured wires.

Compatible with all current connecting hardware in accordance with EN 50173, ISO/IEC 11801 and 60603-x.

### Application

As patch cord in patch panels and as equipment connection cable, especially suitable for CP (Consolidation Point) applications.

For the transmission of digital and analogue voice, video and data signals.

Suitable for all ICT network applications up to class F applications (600 MHz) in accordance with EN 50173-1 and ISO/IEC 11801.

Optimized for the transmission of broadband signals (such as cable TV) in accordance with IEC 15018.

Applicable for Power over Ethernet (PoE) / PoE+ / 4PPoE.

### Construction

Outer sheath material	FRNC/LSZH
-----------------------	-----------

### General properties

Installation temperature	0 °C - +50 °C
Operating temperature	-20 °C - +60 °C
Wire colour	white/blue, white/orange, white/green, white/brown, according to IEC 60189 and IEC 60708
Imprint	DATWYLER «cable type» «additional text» «batch number» «meter marks»
Field of application	Indoor

## Electrical properties

Category	Cat.7
Gbit/s	Up to 10 Gbit/s
Loop resistance at 20 °C	275 Ω/km
Operating capacity	43 pF/m
Impedance at 100 MHz, ±5Ω	100 Ω
NVP %	78
Delay skew	4 ns/100 m
Shielding	shielded
Near end unbalance attenuation LCL at 1-600 MHz	40 dB
Transfer impedance	13 mΩ/m
Coupling attenuation	70 dB
Segregation class	c

Frequency [MHz]	Category	Attenuation [dB] (10M)	NEXT [dB]	PS-NEXT [dB]	ACR-N [dB] (10M)	PS-ACR-N [dB] (10M)	ACR-F [dB] (10M)	Return Loss [dB]
1		0.26	100	97	100	97	100	26
4		0.5	100	97	99	96	99	32
10		0.79	100	97	99	96	99	35
100	5e	2.67	100	97	97	94	97	30
250	6	4.3	95	92	91	88	95	27
500	6 <sub>A</sub>	6.2	92	89	86	83	91	24
600	7	6.71	90	87	83	80	88	23
800		7.9	90	87	82	79	87	21
862		8.3	90	87	82	79	87	21

The performance data given are typical measured values.

## Mechanical properties

Solid / Flex	Stranded wire (flexible)
AWG	26
Minimum bending radius	20 mm
Minimal crush resistance / 10cm	600 N
Minimum number of impacts	10
Repeated bending	1000 cycles

## Standards

Reaction to fire	EN 13501-6
Euroclass	C <sub>ca</sub>
Smoke density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2, AREI-RGIE Section 4.3.3 - applies to FRNC/LS0H
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2, AREI-RGIE Section 4.3.3 SA
Flame propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2, AREI-RGIE Section 4.3.3 F1
Cables standard	ISO/IEC 61156-6, EN 50288-4-2
Cat./Class	Cat.7 / Class F
PoE	IEEE 802.3bt (4PPoE, 100 W), in accordance with ISO/IEC TS 29125 requirements

## Note

PVC versions available

## Versions

Material number	Product	Reaction to fire	Dimensions n x p x [mm <sup>2</sup> (AWG)]	Outer sheath colour	Outer sheath dimensions [mm]	CU rate [kg/km]	Weight [kg/km]	Fire load [kWh/m]	Packing unit	GTIN / EAN
19471600CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	blue	5.8	18	35	0.13	1000 m drum	40393910419658
19472600CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	grey	5.8	18	36	0.13	1000 m drum	40393910419597
19473300CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	yellow	5.8	18	35	0.13	1000 m drum	40393910419535
19473400CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	white	5.8	18	35	0.13	1000 m drum	40393910419474
19473500CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	red	5.8	18	35	0.13	1000 m drum	40393910419412
19473600CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	green	5.8	18	35	0.13	1000 m drum	40393910419351
19473700CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	orange	5.8	18	35	0.13	1000 m drum	40393910419290
19473800CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	black	5.8	18	35	0.13	1000 m drum	40393910419238
19473900CK	CU 7702 4P Flex	Cca-s1,d1,a1	4 x 2 x 0.13 (AWG 26/7)	violet	5.8	18	35	0.13	1000 m drum	40393910419177

Subject to technical modification

As of 2025-05-06 11:25:36