

DCS fanout cable MTP-LCDU, 8 fibres OS2

for splitting 100G into 4x 25G or 40G into 4x 10G



DCS fanout cable MTP-LCDU, 8 fibres OS2

Description

Thin, very flexible fibre-optic fanout cable (round cable, Ø 2.0 mm) with 8 fibres.
Low fire load due to its halogen-free flame-retardant LS0H sheath.
Available with 2.5 m standard length (other lengths on request).
Standard connectivity method can be type A or type C.
Sticker labelling at both cable ends.
Breakout separation is effected with a thin divider housing.
The legs (Ø 2.0 mm) with LCD Uniboot (LCDU) plugs are numbered (1-4).
The legs can be ordered graded in length or of equal length.
Project-specific assemblies are available on request.

Application

MTP-on-LCDU fanout cables are suitable for all high-performance applications in a data centre environment.
All well-known multimode and single-mode QSFP applications such as SR4, PSM4, PLR4 and FCp can be split into four duplex channels using this cable.
The connectivity of this fanout cable splits one 4-channel parallel optic link into four duplex links (e.g. 100G into 4x 25G or 40G into 4x 10G).
The fanout cables are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

Construction

Outer sheath colour	yellow
Outer sheath material	FR/LSZH

Optical Properties

Fibre type	E9/125 G.652.D BLO
Colour code	IEC 60304
Connector type side A	MTP
Connector gender side A	Female (unpinned)
Ferrule polishing connector A	Elite APC 8°
IL maximal, connector A	0.3 dB
IL typical, connector A	0.1 dB
RL minimal, connector A	65 dB
RL typical, connector A	70 dB
Connector type side B	LCDU
Ferrule polishing connector B	PC 0°
IL maximal, connector B	0.25 dB
IL typical, connector B	0.12 dB
RL minimal, connector B	50 dB
RL typical, connector B	55 dB

Mechanical properties

Housing colour connector A	yellow
Housing colour connector B	blue

Scope of delivery

DCS fanout cable (FR/LSOH) with 8 fibres OS2.
 High-performance connector assembly with MTP Elite and LCD Uniboot Intelli-Cross Pro.
 All connectors incl. push-pull tabs.
 Sticker labelling at both cable ends.

Standards

Smoke density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Flame propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2
Flame spread	IEC 60332-3-24
LC standard (IEC)	IEC 61754-20
MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
Polarity standard	TIA-568-C.3 Type A,B,C

Versions

Material number	Product	Number of fibres	Length (m)	Polarity	Number of connectors side A	Number of connectors side B	Number of fibres per connector A	Number of fibres per connector B	Gradation	Weight [kg]	Packing unit	GTIN / EAN
473770	DCS fanout cable 1x MTP - 4x LCDU, equal length	8	2.5	A	1	4	8	2	equal length	0.05 kg	1 pc.	
473771	DCS fanout cable 1x MTP - 4x LCDU, graduated length	8	2.5	A	1	4	8	2	graduated length	0.05 kg	1 pc.	
473775	DCS fanout cable 1x MTP - 4x LCDU, equal length	8	2.5	C	1	4	8	2	equal length	0.05 kg	1 pc.	

Material number	Product	Number of fibres	Length (m)	Polarity	Number of connectors side A	Number of connectors side B	Number of fibres per connector A	Number of fibres per connector B	Gradation	Weight [kg]	Packing unit	GTIN / EAN
473776	DCS fanout cable 1x MTP - 4x LCDU, graduated length	8	2.5	C	1	4	8	2	graduated length	0.05 kg	1 pc.	

MTP® and MTP Elite® are registered brands of US Conec.
Intelli-Cross® is a registered trademark of SEIKOH GIKEN Co., Ltd.