


Polarity: Type A

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TO	BR	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	1A	2A	3A	4A	-	-	-	-	4B	3B	2B	1B

Colour code: DIN (IEC 60304)

Art. No.	Fibre type	Connector type A	Connector colour A	IL mean A [dB]	IL max. A [dB]	RL mean A [dB]	RL min. A [dB]	Connector type B	Connector colour B	IL mean B [dB]	IL max. B [dB]	RL mean B [dB]	RL min. B [dB]	Zero-fibre colour	Length [m]								
47379000ZY	G.652.D BLO	MTP/APC	Yellow	0.10	0.30	70	65	LCDU/APC	Green	0.12	0.25	75	65	Yellow	2.5								
47379200ZY								LCDU/PC	Blue	0.12	0.25	55	50		Turquoise	xx.x							
473770																	Heather violet	0.12	0.25	40	35	Heather violet	xx.x
473772																							
473780	OM3	MTP/PC	Aqua	0.15	0.25	45	35	LCDU/PC	Turquoise	0.12	0.25	40	35	Turquoise	2.5								
473782			Magenta											xx.x									
473750	OM4		Lime	xx.x																			
473752					Lime green	xx.x																	
473760	OM5		xx.x																				
473762				xx.x																			

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor M-Patch 1x12 E9 G.652.D BLO / J-F(ZN)H	-	Yellow	2.0
FO Indoor M-Patch 1x12 G50 OM3 / J-F(ZN)H	-	Turquoise	2.0
FO Indoor M-Patch 1x12 G50 OM4 / J-F(ZN)H	-	Heather violet	2.0
FO Indoor M-Patch 1x12 G50 OM5 / J-F(ZN)H	-	Lime green	2.0

<div><div>Dätwyler IT Infra, itinfra.datwyler.com</div><div>DATWYLER</div></div>			Description DCS fanout cable, 1x MTP-female-4x LCDU, type A, equal					
Drawn	Philipp Bless	16.06.2025	Drawing name DRW_DCS FC_1MTP-f-4LCDU_E_A					
Checked	André Jaun	18.06.2025	Size	Scale	Article number	Document number	Revision	Page
Approved	Kai Wirkus	20.06.2025	A3	-	According to table	-	00	1 of 1