



Polarity: Type C

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TO	BR	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	1B	2B	3B	4B	-	-	-	-	4A	3A	2A	1A

Colour code: DIN (IEC 60304)

Art. No.	Fibre type	Connector type A	Connector colour A	IL mean A [dB]	IL max. A [dB]	RL mean A [dB]	RL min. A [dB]	Connector type B	Connector colour B	IL mean B [dB]	IL max. B [dB]	RL mean B [dB]	RL min. B [dB]	Zero-fibre colour	Length [m]		
47379500ZY	G.652.D BLO	MTP/APC	Yellow	0.10	0.30	70	65	LCDU/APC	Green	0.12	0.25	75	65	Yellow	2.5		
47380100ZY								LCDU/PC	Blue	0.12	0.25	55	50		xx.x		
473776															2.5		
473778															xx.x		
473786	OM3	MTP/PC	Aqua	0.15	0.25	45	35	LCDU/PC						Turquoise	0.12	0.25	40
473788			xx.x														
473756	OM4		Heather violet						Lime green	Lime green	Heather violet	2.5					
473758			xx.x														
473766	OM5		Lime								Lime green	Lime green	2.5				
473768													xx.x				

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
FO Indoor M-Patch 1x12 E9 G.652.D BLO / J-F(ZN)H	-	Yellow	2.0
FO Indoor M-Patch 1x12 G50 OM3 / J-F(ZN)H	-	Turquoise	2.0
FO Indoor M-Patch 1x12 G50 OM4 / J-F(ZN)H	-	Heather violet	2.0
FO Indoor M-Patch 1x12 G50 OM5 / J-F(ZN)H	-	Lime green	2.0

<div><div></div><div>Dätwyler IT Infra, itinfra.datwyler.com</div><div><div></div><div>DATWYLER</div></div></div>			Description DCS fanout cable, 1x MTP-female-4x LCDU, type C, graduated				
Drawn	Philipp Bless	16.06.2025	Drawing name DRW_DCS FC_1MTP-f-4LCDU_G_C				
Checked	André Jaun	18.06.2025	Size	Scale	Article number	Document number	Revision
Approved	Kai Wirkus	20.06.2025	A3	-	According to table	-	00
			Page 1 of 1				