

MTP/PC-f, 0°, Elite,
Magenta housing,
Black push-pull boot

Brady label
white

Brady label
white

MTP/PC-f, 0°, Elite,
Magenta housing,
Black push-pull boot

150 ± 10 mm

150 ± 10 mm

Length [m]

Fibre position
Key up

Fibre position
Key down

Brady label
length [m] art. no.

3 m 473222
3 m 473222

Polarity: Type C (TIA-568.3-D)

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TO	BK	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	2	1	4	3	6	5	8	7	10	9	12	11


Colour code: DIN (IEC 60304)

Art. No.	Description	Polarity	Length [m]
473220	PCC - 1M1FP- 1M1FP -01M0-OM4-RDHV	Type C	1.0
473221	PCC - 1M1FP- 1M1FP -02M0-OM4-RDHV	Type C	2.0
473222	PCC - 1M1FP- 1M1FP -03M0-OM4-RDHV	Type C	3.0
473223	PCC - 1M1FP- 1M1FP -04M0-OM4-RDHV	Type C	4.0
473224	PCC - 1M1FP- 1M1FP -05M0-OM4-RDHV	Type C	5.0
473225	PCC - 1M1FP- 1M1FP -xxMx-OM4-RDHV	Type C	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	45	35

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
M-PATCH J-(ZN)H 12xG50/125 OM4	-	Heather violet	2.0

<div>DATWYLER</div> <div>Dätwyler IT Infra, itinfra.datwyler.com</div>			Description DCS patch cable, MTP/PC-female, OM4, type C					
Drawn	Philipp Bless	28.10.2024	Drawing name		DRW_DCS PC_MTP/PC-f_OM4_C			
Checked	André Jaun	30.10.2024	Size	Scale	Article number	Document number	Revision	Page
Approved	Kai Wirkus	01.11.2024	A4	-	According to table	-	02	1 of 1