

MTP/PC-f, 0°, Elite,
Lime housing,
Black push-pull boot

Brady label
yellow

Brady label
yellow

MTP/PC-f, 0°, Elite,
Lime housing,
Black push-pull boot

150 ± 10 mm

150 ± 10 mm

Length [m]

Fibre position
Key up

Fibre position
Key up

Brady label
length [m] art. no.

3 m 473242
3 m 473242

Polarity: Type B (TIA-568.3-D)

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TO	BK	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	12	11	10	9	8	7	6	5	4	3	2	1


Colour code: DIN (IEC 60304)

Art. No.	Description	Polarity	Length [m]
473240	PCB - 1M1FP- 1M1FP -01M0-OM5-RDLG	Type B	1.0
473241	PCB - 1M1FP- 1M1FP -02M0-OM5-RDLG	Type B	2.0
473242	PCB - 1M1FP- 1M1FP -03M0-OM5-RDLG	Type B	3.0
473243	PCB - 1M1FP- 1M1FP -04M0-OM5-RDLG	Type B	4.0
473244	PCB - 1M1FP- 1M1FP -05M0-OM5-RDLG	Type B	5.0
473245	PCB - 1M1FP- 1M1FP -xxMx-OM5-RDLG	Type B	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	45	35

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
M-PATCH J-(ZN)H 12xG50/125 OM5	-	Lime green	2.0

<div><div>Dätwyler IT Infra, itinfra.datwyler.com</div><div>DATWYLER</div></div>			Description DCS patch cable, MTP/PC-female, OM5, type B						
Drawn	Philipp Bless	28.10.2024	Drawing name		DRW_DCS PC_MTP/PC-f_OM5_B				
Checked	André Jaun	30.10.2024	Size	Scale	Article number	Document number	Revision	Page	
Approved	Kai Wirkus	01.11.2024	A4	-	According to table	-	02	1 of 1	