

Brady label
length [m] art. no.

3 m 473262

Polarity: Type A (TIA-568.3-D)

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TQ	BK	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	1	2	3	4	5	6	7	8	9	10	11	12


Colour code: DIN (IEC 60304)

Art. No.	Description	Polarity	Length [m]
473260	PCA - 1M1FA- 1M1FA -01M0-OS2-RDYE	Type A	1.0
473261	PCA - 1M1FA- 1M1FA -02M0-OS2-RDYE	Type A	2.0
473262	PCA - 1M1FA- 1M1FA -03M0-OS2-RDYE	Type A	3.0
473263	PCA - 1M1FA- 1M1FA -04M0-OS2-RDYE	Type A	4.0
473264	PCA - 1M1FA- 1M1FA -05M0-OS2-RDYE	Type A	5.0
473265	PCA - 1M1FA- 1M1FA -xxMx-OS2-RDYE	Type A	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
SM/APC	0.10	0.30	70	65

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
M-PATCH J-(ZN)H 12x E9/125 G.652.D BLO	-	Yellow	2.0

 Dätwyler IT Infra, itinfra.datwyler.com DATWYLER			Description DCS patch cable, MTP/APC-female, G.652.D BLO, type A					
Drawn	Philipp Bless	28.10.2024	Drawing name		DRW_DCS PC_MTP/APC-f_OS2_A			
Checked	André Jaun	30.10.2024	Size	Scale	Article number	Document number	Revision	Page
Approved	Kai Wirkus	01.11.2024	A4	-	According to table	-	02	1 of 1