

MTP/PC-f, 0°, Elite,  
Aqua housing,  
Black push-pull boot

Brady label  
white

Brady label  
white

MTP/PC-f, 0°, Elite,  
Aqua housing,  
Black push-pull boot

150 ± 10 mm

150 ± 10 mm

Length [m]

Fibre position  
Key up

Fibre position  
Key down

Brady label  
length [m] art. no.

3 m 475202  
3 m 475202

Polarity: Type A (TIA-568.3-D)

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TQ	BK	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	1	2	3	4	5	6	7	8	9	10	11	12


Colour code: DIN (IEC 60304)

Art. No.	Description	Polarity	Length [m]
475200	PCA - 1M1FP- 1M1FP-01M0-OM3-RDTQ	Type A	1.0
475201	PCA - 1M1FP- 1M1FP-02M0-OM3-RDTQ	Type A	2.0
475202	PCA - 1M1FP- 1M1FP-03M0-OM3-RDTQ	Type A	3.0
475203	PCA - 1M1FP- 1M1FP-04M0-OM3-RDTQ	Type A	4.0
475204	PCA - 1M1FP- 1M1FP-05M0-OM3-RDTQ	Type A	5.0
475205	PCA - 1M1FP- 1M1FP-xxMx-OM3-RDTQ	Type A	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	45	35

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
M-PATCH J-(ZN)H 12xG50/125 OM3	-	Turquoise	2.0

<div> <b>DATWYLER</b></div> <div>Dätwyler IT Infra, itinfra.datwyler.com</div>			Description <b>DCS patch cable, MTP/PC-female, OM3, type A</b>						
Drawn	Philipp Bless	28.10.2024	Drawing name		DRW_DCS PC_MTP/PC-f_OM3_A				
Checked	André Jaun	30.10.2024	Size	Scale	Article number	Document number	Revision	Page	
Approved	Kai Wirkus	01.11.2024	A4	-	According to table	-	01	1 of 1	