



1	2	3	4	5	6	7	8
A							
B							
C							
D							
E							
F							
1	2	3	4	5	6	7	8

Type					IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC					0.15	0.25	45	35

Cable description				CPR class	Sheath colour	Sheath Ø [mm]
M-PATCH J-(ZN)H 12xG50/125 OM3				-	Turquoise	2.0

Art. No.				Description	Polarity	Length [m]
475210				PCB - 1M1FP- 1M1FP -01M0-OM3-RDTQ	Type B	1.0
475211				PCB - 1M1FP- 1M1FP -02M0-OM3-RDTQ	Type B	2.0
475212				PCB - 1M1FP- 1M1FP -03M0-OM3-RDTQ	Type B	3.0
475213				PCB - 1M1FP- 1M1FP -04M0-OM3-RDTQ	Type B	4.0
475214				PCB - 1M1FP- 1M1FP -05M0-OM3-RDTQ	Type B	5.0
475215				PCB - 1M1FP- 1M1FP -xxMx-OM3-RDTQ	Type B	xx.x

Note: Some items in different lengths may not have been included in this table.			
---	--	--	--

Dätwyler IT Infra, itinfra.datwyler.com			Description					
DATWYLER			DCS patch cable, MTP/PC-female, OM3, type B					
Drawn	Philipp Bless	28.10.2024	Drawing name		DRW_DCS PC_MTP/PC-f_OM3_B			
Checked	André Jaun	30.10.2024	Size	Scale	Article number	Document number	Revision	Page
Approved	Kai Wirkus	01.11.2024	A4	-	According to table	-	01	1 of 1