

1	2	3	4	5	6	7	8
A							A
B							B
C							C
D							D
E							E
F							F

MTP/PC-f, 0°, Elite, Aqua housing, Black push-pull boot

Brady label white

150 ± 10 mm

Length [m]

Brady label white

150 ± 10 mm

MTP/PC-f, 0°, Elite, Aqua housing, Black push-pull boot

Optical fibre, 250 µm

Aramid yarn

LS0H sheath

2.0 mm

Fibre position Key up

Fibre position Key down

Brady label length [m] art. no.

3 m 475222

3 m 475222

Polarity: Type C (TIA-568.3-D)

Colour	RD	GN	BU	YE	WH	GY	BN	VT	TQ	BK	OG	PK
Side A	1	2	3	4	5	6	7	8	9	10	11	12
Side B	2	1	4	3	6	5	8	7	10	9	12	11


Colour code: DIN (IEC 60304)

Art. No.	Description	Polarity	Length [m]
475220	PCC - 1M1FP- 1M1FP -01M0-OM3-RDTQ	Type C	1.0
475221	PCC - 1M1FP- 1M1FP -02M0-OM3-RDTQ	Type C	2.0
475222	PCC - 1M1FP- 1M1FP -03M0-OM3-RDTQ	Type C	3.0
475223	PCC - 1M1FP- 1M1FP -04M0-OM3-RDTQ	Type C	4.0
475224	PCC - 1M1FP- 1M1FP -05M0-OM3-RDTQ	Type C	5.0
475225	PCC - 1M1FP- 1M1FP -xxMx-OM3-RDTQ	Type C	xx.x

Note: Some items in different lengths may not have been included in this table.

Type	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
MM/PC	0.15	0.25	45	35

Cable description	CPR class	Sheath colour	Sheath Ø [mm]
M-PATCH J-(ZN)H 12xG50/125 OM3	-	Turquoise	2.0

Dätwyler IT Infra, itinfra.datwyler.com			Description					
 DATWYLER			DCS patch cable, MTP/PC-female, OM3, type C					
Drawn	Philipp Bless	28.10.2024	Drawing name		DRW_DCS PC_MTP/PC-f_OM3_C			
Checked	André Jaun	30.10.2024	Size	Scale	Article number	Document number	Revision	Page
Approved	Kai Wirkus	01.11.2024	A4	-	According to table	-	01	1 of 1