

FL – PVC – unsupported

Low rise - travelling height maximum 80m



Drawing according to article number 167046 - Type 8326-F



Descrizione

Elevator suspension cable for indoor and panoramic elevators

Applicazione

To comply with the correct installation procedures please refer to the Datwyler installation manual which is available separately

Costruzione

Core flexible	class 5
Core insulation	PVC
Supporting members	none

Proprietà generali

Coax	grigio
Core	black, white numbered, G = with green-yellow core(s), JIS compliant types with different colours
Pair/quad	various colours or black with white numbers
Operating temperature	-15 °C - +70 °C
Colore della guaina esterna	grigio
Materiale della guaina esterna	PVC

Proprietà elettriche

Rated voltage U ₀ /U	according to table
---------------------------------	--------------------

Proprietà meccaniche

Acceleration	0,8 m/s ²
Maximum free suspension	45 m
Maximum running speed	4 m/s
Maximum travelling height	80 m
Recommended loop diameter	according to table, tolerance -50/+100 mm

Standards

Standard per cavi flessibili di controllo dell'ascensore

EN 50214

Versioni

Codice art.	Prodotto	Area sezione trasversale [n x mm ²]	Tensione nominale [V]	Loop [mm]	Suspension device	Design del cavo	Supporting members	Elementi di dati	Dimensioni esterne	Tasso di CU [kg/km]	Weight [kg/km]	GTIN / EAN
181658	8304-F	3 G 1.50 9 x 0.75	450/750 300/500	350	LZ 1006	3 G 1.50 + 9 x 0.75 + 3 x 2 x 0.50 mm ² (FTP)	none	3 x 6651-F	5.5 mm x 48.6 mm	143	442	
185358	8798-F	12 G 0.75	300/500	400	LZ 1006	12 G 0.75 mm ² + 1 CX 75 Ω	none	1 x HF-2122-F	6.5 mm x 42.3 mm	111	427	
167046	8326-F	20 x 0.75	300/300	350	LZ 1006	20 x 0.75 + 2 x 2 x 0.50 mm ² (FTP)	none	2 x 6651-F	5.3 mm x 52.0 mm	169	467	
184758	8387-F	24 G 0.75	300/500	350	LZ 1009	24 G 0.75 + 2 x 4 x 0.25 mm ² (STQ)	none	2 x 7954/2-F	5.5 mm x 73.0 mm	216	695	
167577	8506-F	4 x 1.50 2 x 1.00	450/750 300/500	400	LZ 1006	4 x 1.50 + 2 x 1.00 + 2 x 4 x 0.50 mm ² (STQ)	none	2 x 8504-F	7.6 mm x 34.1 mm	141	422	
182298	8822-F	4 G 2.50 12 x 1.00	450/750 300/500	400	LZ 1009	4 G 2.50 + 12 x 1.00 + 2 x 2 x 0.34 mm ² (FTP) + 1 CX 75 Ω	none	2 x 7345-F + 1 x HF-2122-F	6.5 mm x 67.7 mm	254	767	
185281	8304-F	12 G 1.00	300/500	350	LZ 1006	12 G 1.00 + 2 x 2 x 0.50 mm ² (FTP)	none	2 x 6651-F	5.4 mm x 46.0 mm	140	421	
181023	8606-F	3 G 2.50 14 x 1.00	450/750 300/500	350	LZ 1009	3 G 2.50 + 14 x 1.00 + 4 x 2 x 0.34 mm ² (FTP)	none	4 x 7345-F	5.7 mm x 72.0 mm	244	724	
173814	8548-F	4 x 1.50	450/750	400	LZ 1006	4 x 1.50 + 2 x 4 x 0.50 mm ² (STQ) + 1 CX 75 Ω	none	2 x 8504-F + 1 x HF-2122-F	7.4 mm x 32.9 mm	146	398	
167019	8216-F	2 x 1.50	450/750	400	LZ 1006	2 x 1.50 + 8 x 2 x 0.50 mm ² (FTP) + 1 CX 75 Ω	none	8 x 6651-F + 1 x HF-2122-F	7.0 mm x 46.3 mm	149	492	
167567	8447-F			400	LZ 1006	10 x 2 x 0.75 mm ² (FTP)	none	10 x 6651-F	6.4 mm x 46.2 mm	171	454	
191032	8867-F			500	LZ 1006	4 x 4 x 2 x AWG 26 (S/FTP)	none	4 x HF-4367-F	8.4 mm x 29.4 mm	71	321	

Con riserva di modifiche tecniche

A partire da 2021-08-05 08:33:41