



FO-DCS 3U/7HP splice plug-in modules, 6x LCQ, OS2

for FO-DCS modular subracks / panels

with 2x 12 pigtails OM3, OM4, OS2 and 6 LCQ adapters



High-performance FO-DCS splice plug-in modules, 24F, 3U/7HP

Descrizione

Polycarbonate (PC) housing with press-fit side panels and polycarbonate (black) or aluminium front panel (3U/7HP).

Equipped with 2 splice cassettes for 12 fibres per cassette.

Splice cassettes have splice reserve on both sides (cable / pigtail), splice comb and strain relief.

Black PC front panels provide labelling strips on both sides of the LCQ ports for customer-specific printing.

Fixed with two knurled screws (captive).

There is a separate distribution box available for the partition of multi-fibre loose tube cables or for storing the excess tube lengths.

Applicazione

FO-DCS splice plug-in modules are suitable for all high-performance applications with duplex signals, particularly in the data centre environment.

They find modular application in FO-DCS modular panels (19"/1U) or in FO-DCS subracks (19"/3U, 19"/4U).

They are used to accept fibre optic cables which are spliced in-situ.

Packing densities of up to 288 fibres on 3U are achieved with these plug-in modules.

They are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

Proprietà generali

Acceptance capacity	12 LC duplex ports (24 fibres)
Fully equipped	sì
System	FO-DCS
Dimensioni esterne	3 U, 129 mm x 35 mm x 180 mm

Proprietà ottiche

Adapter colour, front side	blu
Adapter material, front side	Polimerico
Adattatore, lato anteriore	6 x LCQ/PC, blu (Dust plug)
Connector type, front side	LC
Connettori, lato anteriore	12 x LC/PC 0°
Ferrule material, front side	Zirconia (ZrO ₂)
Ferrule polishing, front side	PC 0°
Insertion loss (IL), maximal, front side	0,25 dB
Insertion loss (IL), typical, front side	0,1 dB
Materiale manicotto, lato anteriore	Zirconia (ZrO ₂)
Number of adapters, front side	6
Number of connectors, front side	12
Return loss (RL), minimal, front side	35 dB
Return loss (RL), typical, front side	40 dB
Tipo di adattatore, lato anteriore	LCQ/PC
Tipologia di fibra	E9/125 OS2

Proprietà meccaniche

Dust protection, frontside	sì
Dust/Laser protection, frontside	Dust plug
Laser protection, frontside	no

Ambito di consegna

Housing with front panel, equipped with 6 LC Quad adapters (ceramic sleeves).
 Rear fitted with two M12 cable entries.
 2 splice cassettes with cover and splice comb (each for 12 fibres).
 2 pigtail sets (1.3 m), 12x LC per set (ceramic ferrules).

Versioni

Codice art.	Prodotto	Colore	Materiale	Peso [kg]	Unità di imballaggio	GTIN / EAN
57153200ZY	FO-DCS 3U/7HP splice plug-in module, 6x LCQ/PC, OS2 (G.652.D)	nero	Polycarbonate (PC)	0,3 kg	1 pc.	40393910006322