


## FO Indoor Mini Zipcord / I-V(ZN)H

1.8 mm, LS0H, Euroclass Fca

Tight buffer

flame retardant - IEC 60332.1



- 1 Fibre
- 2 Tight buffer: 600 µm
- 3 Aramid yarn
- 4 Single-fibre cable: 1.8 mm



### Descrizione

Very thin and flexible Mini Zipcord with tight buffers 0.6 mm.  
 The ends can easily be split into two single cables.  
 Flame retardant halogen-free LS0H sheath.  
 Very low fire load.

### Applicazione

Suitable for patch cables between terminal distributors and/or end devices.  
 For direct termination with Simplex or Duplex connectors.

### Costruzione

Materiale della guaina esterna	FRNC/LSZH
--------------------------------	-----------

### Proprietà generali

Massimo numero di fibre	2
Installation temperature	-10 °C - +50 °C
Operating temperature	-20 °C - +60 °C
Impronta	DATWYLER «cable type» «Datwyler designation» «DIN designation» «no. of fibres» «fibre type» «add. text» «batch no.» «meter marks»
Campo di applicazione	Interno

## Standards

Tensile performance	IEC 60794-1-21 E1
Crush resistance	IEC 60794-1-21 E3
Impact	IEC 60794-1-21 E4
Repeated bending	IEC 60794-1-21 E6
Torsion	IEC 60794-1-21 E7
Bend	IEC 60794-1-21 E11
Variazione di temperatura	IEC 60794-1-22 F1
Reaction to fire	EN 13501-6
Euroclass	F <sub>ca</sub>
Densità del fumo	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2
Zero alogeni nessun gas corrosivo	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Propagazione della fiamma	EN 60332-1-2, IEC 60332-1-2, VDE 0482-332-1-2

## Versioni

Codice art.	Prodotto	Reaction to fire	Colore della guaina esterna	Fibre type	Categoria di fibra	Outer sheath material	Raggio di curvatura [mm]	Dimensioni della guaina esterna [mm]	Weight [kg/km]	Tensile load [N]	Crush resistance short term [N]	Fire load [kWh/m]	Unità di imballaggio	GTIN / EAN
19024700FZ	FO Indoor Mini Zip-cord	Fca	verde	E9/125 G.652.D OS2	OS2	FRNC/LSZH	50	3.7 x 1.8	5	150	800	0,052	al metro	
19030600FZ	FO Indoor Mini Zip-cord	Fca	giallo	E9/125 G.652.D OS2	OS2	FRNC/LSZH	50	3.7 x 1.8	5	150	800	0,052	al metro	
19346500FZ	FO Indoor Mini Zip-cord	Fca	giallo	E9/125 G.657.A2 OS2	OS2	FRNC/LSZH	50	3.7 x 1.8	5	150	800	0,052	al metro	
18603800FZ	FO Indoor Mini Zip-cord	Fca	turchese	G50/125 OM3	OM3	FRNC/LSZH	50	3.7 x 1.8	5	150	800	0,052	al metro	
19346800FZ	FO Indoor Mini Zip-cord	Fca	heather violet	G50/125 OM4	OM4	FRNC/LSZH	50	3.7 x 1.8	5	150	800	0,052	al metro	

Con riserva di modifiche tecniche

A partire da 2024-06-27 11:36:13