

DIN rail breakout distribution box

OS2

with adapters



DIN rail breakout distribution box, loaded with 6 LSH/APC adapters

Description

Patch panel (breakout box) for terminating pre-assembled fibre optic cables in distribution or connection boxes, maximum 24 fibres.
For mounting on support or top-hat rail (DIN rail TH35).
Top-hat rail fastening mounted centrally, possibility of asymmetrical fastening.
Loaded with FO adapters.

General properties

Dimensions	135 x 38 x 141 mm
Colour	similar to RAL 7035
Outer dimensions (HxWxD)	38 mm x 135 mm x 141 mm
Housing	aluminium
Imprint	label strips
Cable entry	two cable entry openings and one M20 gland
Strain relief	by screwed cable gland
Capacity	up to 24 fibres

Optical Properties

Adapter	LCD, LCQ, LSH or SCD with ceramic sleeves
Fibre class	Singlemode
Fibre category	OS2
Ferrule material	Zirconia

Scope of delivery

- DIN rail breakout distribution box
- straight cable entry (right and left or rear)
 - FO adapters, fastened by screws
 - labelling strip
 - cable gland (1x M20)

Note

Wall mounting is possible with additional mounting brackets.

Versions

Material number	Product	Number of adapters	Adapter	Colour (Adapter)	Weight [kg]	GTIN / EAN
41563401ZY	DIN rail breakout distribution box	6	SCD/PC	blue	0.35 kg	40393910232912
41564301ZY	DIN rail breakout distribution box	6	SCD/APC	green	0.35 kg	40393910232929
41563301ZY	DIN rail breakout distribution box	6	LCD/PC	blue	0.35 kg	40393910232868
41564600ZY	DIN rail breakout distribution box	6	LCD/APC	green	0.35 kg	40393910232646
41563901ZY	DIN rail breakout distribution box	6	LCQ/PC	blue	0.35 kg	40393910232875
41564101ZY	DIN rail breakout distribution box	6	LCQ/APC	green	0.35 kg	40393910232882
41563501ZY	DIN rail breakout distribution box	6	LSH/APC	green	0.35 kg	40393910232899
41564001ZY	DIN rail breakout distribution box	12	LSH/APC	green	0.35 kg	40393910232905

Variants on request.

Subject to technical modification

As of 2024-01-26 12:29:35