

FO duplex patch cord ST/PC - ST/PC

G50/125 OM3, Duplex Fig. 8



image similar

Description

Datwyler offers a broad range of terminated connectors for individual customer needs.

Construction

Cable	Duplex Fig. 8
Cable construction	I-V(ZN)H (4.1 x 2.0mm)
Outer sheath colour	turquoise

General properties

Operating temperature	-10 °C - +60 °C
-----------------------	-----------------

Optical Properties

Lifetime	1000 connections with stable attenuation values
Reproducibility of the IL	a maximum of +/- 0.1dB
Fibre type	G50/125 OM3
Ferrule material	Zirconia
Connector type side A	ST/PC
IL maximal, connector A	0.25 dB
IL typical, connector A	0.15 dB
RL minimal, connector A	30 dB
RL typical, connector A	35 dB
Grade IEC61755, connector A (better than)	Bm2m
Standard connector A	IEC 61754-2
Connector type side B	ST/PC
IL maximal, connector B	0.25 dB
IL typical, connector B	0.15 dB
RL minimal, connector B	30 dB
RL typical, connector B	35 dB
Grade IEC61755, connector B (better than)	Bm2m
Standard connector B	IEC 61754-2

Mechanical properties

Bending (IEC 60794-1-21 E11, reversible fibre attenuation)	≤ 0,5 dB
Connector cable retention	100 N
Crush resistance (IEC 60794-1-21 E3, reversible fibre attenuation)	≤ 0,2 dB
Tensile load (IEC 60794-1-21 E1 0,33% reversible fibre elongation)	200 N
Torsion (IEC 60794-1-21 E7, reversible fibre attenuation)	≤ 0,1 dB

Standards

Impact	IEC 60794-1-21 E4
Repeated bending	IEC 60794-1-21 E6

Versions

Material number	Product	Length (m)	Weight [kg]	GTIN / EAN
42223108ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	1	0.03 kg	40393910085952
42223208ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	2	0.04 kg	40393910085945
42223308ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	3	0.04 kg	40393910085938
42223408ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	4	0.05 kg	40393910085921
42223508ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	5	0.06 kg	40393910085914
42223608ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	6	0.07 kg	40393910085907
42223708ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	7	0.08 kg	40393910085891
42223808ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	8	0.08 kg	40393910085884
42223908ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	9	0.09 kg	40393910085877
42224008ZY	FO duplex patch cord ST/PC - ST/PC, G50/125 OM3	10	0.1 kg	40393910085860

