


## JE-H(St)H...Bd FE180 E30-E90

Wiring cable for industrial electronics, max. 225V, Keram

halogen-free, with improved fire characteristics,  
with reference to VDE 0815,  
circuit integrity (FE180) in accordance with VDE 0472-814, IEC 60331, EN 50200,  
System Circuit Integrity E30-E90\* in accordance with DIN 4102-12



- 1 Conductor: solid
- 2 Insulation: cross-linked polymer, zero halogen
- 3 Drain wire: Ø 0.8 mm
- 4 Separator: plastic tape, zero halogen
- 5 Shielding: Al-laminated tape, zero halogen
- 6 Sheath: FRNC/LSZH



### Description

Cables with intrinsic fire resistance are installed in all areas that require special protection of people and equipment against fire and fire damages and where strict security requirements must be fulfilled. Suitable for indoor applications. For outdoor applications, protection must be provided against exposure to direct sunlight. The cable should only be laid directly in earth or water if a protective conduit is used. These cables correspond to the demands of System Circuit Integrity E30-E90\* in accordance with DIN 4102-12. System Circuit Integrity is guaranteed at an operating voltage up to 110V. Permitted operating temperature at conductor of +70°C.

### Construction

Conductor	Bare copper, solid, 0.8 mm diameter, VDE 0815
Insulation	Fire-resistant, cross-linked, high-performance Keram special compound, EN 50290-2-36
Core colours	VDE 0815
Shielding	Al-laminated tape with copper drain wire Ø 0.8 mm
Outer sheath material	Flame retardant polyolefin compound VDE 0819-107, EN 50290-2-27 and VDE 0250-214 "HM 2"

### General properties

Circuit Integrity	E90
Insulation integrity	FE 180
Installation temperature	-5 °C - +50 °C
Operating temperature	-30 °C - +70 °C

## Electrical properties

Capacitive coupling 0,8 mm, 100m @ 800Hz	200 pF/km
Maximum loop resistance 0,8 mm	73.2 Ω/km
Minimum insulation resistance	100 MΩ x km
operating capacity, 1km @ 800Hz	120 nF/km
peak voltage	225 V
Test voltage 50Hz, core/core	500 V
Test voltage 50Hz, core/screen	2,000 V

## Mechanical properties

Minimal crush resistance / 10cm	1,000 N
Minimum bending during installation (multi core)	7.5 x D
Minimum bending radius permanent (multi core)	7.5 x D

## Standards

Insulation Integrity (FE180)	IEC 60331-11/-21 (180 minutes), VDE 0472-814 (FE180), BS 6387 C/W/Z, IEC 60331-1 (120 minutes), IEC 60331-2 (120 minutes), EN 50200 (PH120 minutes), NBN 713-020, VDE 0482-200 (PH120), AREI-RGIE Art.104-FR1
System circuit integrity	DIN 4102-12, AREI-RGIE Art.104-FR2
Smoke density	IEC 61034-1/-2, EN 61034-1/-2, VDE 0482-1034-1/-2, AREI-RGIE Art.104-SD
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2, AREI-RGIE Art.104-SA
Flame propagation	IEC 60332-1-2, EN 60332-1-2, VDE 0482-332-1-2, AREI-RGIE Art.104-F1
Flame spread	IEC 60332-3-22/-24, EN 60332-3-22/-24, VDE 0482-332-3-22/-24, AREI-RGIE Art.104-F2

## Note

System Circuit Integrity is dependent on installation method.

## Versions

Material number	Product	Outer sheath colour	Outer sheath diameter [mm]	CU rate [kg/km]	Weight [kg/km]	Fire load [kWh/m]	Weight [kg]	Packing unit	GTIN / EAN
188092	JE-H(St)H...Bd FE180 E30-E90 1x2x0.8 mm	orange	5.6	15	42	0.095		by the metre	40393910073171
18809700ZK	JE-H(St)H...Bd FE180 E30-E90 2x2x0.8 mm	orange	6.1	25	57	0.123		1000 m drum	40393910035384
18809700ZL	JE-H(St)H...Bd FE180 E30-E90 2x2x0.8 mm	orange	6.1	25	57	0.123		500 m drum	40393910035377
18809700ZZ	JE-H(St)H...Bd FE180 E30-E90 2x2x0.8 mm	orange	6.1	25		0.123	0.06 kg	by the metre	40393910035360
188099	JE-H(St)H...Bd FE180 E30-E90 4x2x0.8 mm	orange	9	45	101	0.21		by the metre	40393910073119
188102	JE-H(St)H...Bd FE180 E30-E90 8x2x0.8 mm	orange	13.9	85	221	0.52		by the metre	40393910073096
188104	JE-H(St)H...Bd FE180 E30-E90 12x2x0.8 mm	orange	14.8	126	280	0.58		by the metre	40393910073072

Material number	Product	Outer sheath colour	Outer sheath diameter [mm]	CU rate [kg/km]	Weight [kg/km]	Fire load [kWh/m]	Weight [kg]	Packing unit	GTIN / EAN
188108	JE-H(St)H...Bd FE180 E30-E90 20x2x0.8 mm	orange	18.8	206	421	0.80		by the metre	40393910073034
188106	JE-H(St)H...Bd FE180 E30-E90 16x2x0.8 mm	orange	16.6	166	324	0.69		by the metre	40393910073058
188111	JE-H(St)H...Bd FE180 E30-E90 32x2x0.8 mm	orange	22	326	589	1.02		by the metre	40393910073003
188113	JE-H(St)H...Bd FE180 E30-E90 40x2x0.8 mm	orange	25.5	407		1.38	0.76 kg	by the metre	40393910072983
188115	JE-H(St)H...Bd FE180 E30-E90 52x2x0.8 mm	orange	27.8	529		1.59	0.93 kg	by the metre	40393910072969

Additional dimensions available on request.

Subject to technical modification

As of 2023-10-30 08:22:38