


## KS-T 5 1/8 tool-less Cat.5e

RJ45 module, shielded, Category 5e

for 1GBase-T



KS-T 5 1/8 tool-less RJ45 module, Cat.5e, shielded



### Description

The KS-T 5 1/8 tool-less RJ45 module is a module that is designed to shorten the termination and installation time. For the transmission of digital and analogue voice, video and data signals. Applicable for the transmission of all applications up to Class D (e. g. 1GBase-T). Solid zinc die casting housing with mounting clip for installation in Keystone panels and outlets. Contact spring with phosphor bronze alloy, plated with gold. For connecting the wires a wire manager is used in combination with two integrated moveable housing wings for tool-less IDC connections. Only for cutting the wires a plane wire cutter is necessary. The 360° metal shield protects the module and guarantees stable electric performance. Strain relief via cable tie. The module is re-usable.

### General properties

|                          |                 |
|--------------------------|-----------------|
| Installation temperature | -10 °C - +60 °C |
| Storage temperature      | -40 °C - +70 °C |
| Operating temperature    | -20 °C - +60 °C |

### Electrical properties

|           |                |
|-----------|----------------|
| Gbit/s    | Up to 1 Gbit/s |
| Shielding | shielded       |

### Mechanical properties

|                          |   |
|--------------------------|---|
| Connection type          | IDC insulation displacement connectors                                    |
| Solid copper wire        | 0.50 (AWG 24) - 0.65 (AWG 22)   |
| Stranded copper wire     | AWG26/7   |
| Diameter over Insulation | 0.70 mm - 1.40 mm   |
| Re-connection            | for AWG 22, AWG 23 and AWG 24 when using the same or bigger wire diameter |
| Re-usable                | once  |

## Standards

|                     |  |
|---------------------|--|
| Cat./Class          | Cat.5e / Class D                         |
| PoE                 | IEEE 802.3bt Type 4 (100W)               |
| Connector standards | IEC 60603-7-3                            |
| Cabling standards   | ISO/IEC 11801, EN 50173-1, TIA/EIA 568-x |

## Versions

| Material number | Product  | Colour | Weight [kg] | Packing unit | GTIN / EAN     |
|-----------------|--|--------|-------------|--------------|----------------|
| 418055          | RJ45 module KS-T 5 1/8 tool-less Cat.5e shielded | silver | 0.02 kg     | 10 pcs.      | 40393910165135 |

Subject to technical modification

As of 2023-09-14 07:59:41