

## MD-DCS splice panel 19" 1U, 96 fibres

Extendable, to accept 4 MD-DCS snap-in modules



### Description

Sturdy steel housing with cover 19"/1U, Black powder coating RAL 9005.

For termination of fibre optic cables via splice.

Including splice cassettes for crimp splice protectors.

Allows for variable port density and connector combinations between LCD, SCD for splicing and inclusion of MTP for preterminated connections.

Modular and scalable system for variable fiber densities from lowest 12 fibers (SCD) to 288 fibers (MTP) per U.

### Application

Modular, scalable medium-density platform for server room and data centre environment.

Variable port densities of up to 48 LCD ports or 24 SCD ports.

This allows for up to 96 fibers with LCD or 48 fibers with SCD per spliced.

Mixing with pre-terminated trunk cables is possible.

### General properties

System	MD-DCS
Outer dimensions (HxWxD)	1 U, 44.0 mm x 482.6 mm x 292.5 mm
Housing	Black powder coated steel, integrated 19"/1U fixation on the front
Cable entry	rear left and right with pre-stamped cable entries M20 - these pre-stamped holes can be opened as necessary
Extractable drawer	yes

### Scope of delivery

19"/1U panel (19" mounting brackets) with integrated cable support plate (without plug-in modules)

Includes 4 splice cassettes

Screws, Cage Nuts, Cable Ties, Velcro Tape Strips

## Versions

Material number	Product	Weight [kg]	Packing unit	GTIN / EAN
476123	MD-DCS splice panel 19" 1U, 96 fibres	2 kg	1 pc.	40393910216400



Subject to technical modification

As of 2024-03-14 09:34:37