

MD-DCS Breakout-Panel 19" 2U, 8x 6/12-Port

to accept 8 MD-DCS Snap-In modules



Description

Sturdy steel housing with cover 19"/2U, Black powder coating RAL 9005.
 Pre-assembled for direct installation into network and server racks. Acceptes up to 8 MD-DCS Snap-In modules and/or blind covers.
 Allows for variable port density and connector combinations beetween LCD, SCD and MTP
 Modular and scalable system for variable fiber densities from lowest 12 fibers (SCD) to 288 fibers (MTP) per RU

Application

Modular, scalable medium-density platform for server room and data centre environment
 Variable port densities of up 96 LCD ports or 48 MTP ports.
 This allows for up to 192 fibers with LCD or 576 fibers with MTP₁₂ per height unit

General properties

Acceptance capacity	8 MD-DCS Snap-In modules
System	MD-DCS
Outer dimensions (HxWxD)	2 U, 88.1 mm x 482.6 mm x 292.5 mm
Housing	Black powder coated steel, integrated 19"/2U fixation on the front
Cable entry	rear left and right with holes for M10 and M12 cable glands, left, mid, right cut outs for 1 OV cable entry modular plates
Extractable drawer	no

Scope of delivery

19"/2U panel (19" mounting brackets) with
 integrated cable support plate
 (without plug-in modules)
 Screws, Cage Nuts, Cable Ties, Velcro Tape Strips

Versions

Material number	Product	Weight [kg]	Packing unit	GTIN / EAN
476116	MD-DCS Breakout-Panel 19" 2U, 8x 6/12-Port	4.7 kg	1 pc.	40393910216332



Subject to technical modification

As of 2024-03-04 12:09:58