

## Breakout box OV-S

19"/1 U, OS2, LSH-C/APC

with adapters, labelling strip and mounting set



### Description

For the termination of pre-assembled fibre optic cables.  
Loaded with a maximum of 12 / 24 FO adapters.

### General properties

System	OV-S breakout
Outer dimensions (HxWxD)	1 U, 42 mm x 482.2 mm x 245 mm
Housing	metal sheet, black, extractable drawer with locking mechanism, box allows for depth-adjustable mounting (5 steps, maximum 50 mm)
Front plate	similar to RAL 7035, similar to RAL 9005 or stainless steel
Imprint	numbers (silk screen printing) on frontplate
Cable entry	rear left and right with pre-stamped cable entries M15, M20 and M25 - these pre-stamped holes can be opened as necessary
Strain relief	with cable tie and screwed cable gland (M20)
Capacity	up to 48 fibres
Labelling strip included	yes
Mounting set included	yes
Extractable drawer	yes
Fold-down drawer	no

### Optical Properties

Fibre class	Singlemode
Fibre category	OS2
Adapter	LSH-C/APC
Adapter colour	green

### Scope of delivery

Breakout box with  
 - two straight cable entries  
 - FO adapters, fastened by screws  
 - labelling strip  
 - mounting set

### Versions

Material number	Product	Colour (Frontplate)	Number of adapters	Adapter orientation	Weight [kg]	Packing unit	GTIN / EAN
41511801ZY	Breakout box OV-S 24xLSH-C/APC	light grey	24	vertical	2.93 kg	1 pc.	40393910014112

Variants on request.



Subject to technical modification

As of 2024-04-19 07:08:49