

UP/UP-K Outlet CSA Plus 2/8 (1/8)

shielded, Category 6_A
flush/duct mounted & floor boxes

with 1 or 2 RJ45 jacks Cat. 6A (IEC) shielded, angled



1

2

1 Data outlet CSA Plus 2/8 Cat.6A
with central plate

2 Data outlet CSA Plus 1/8 Cat.6A
with central plate

Description

Data outlet CSA Plus Cat. 6A shielded, angled, for the transmission of digital and analogue voice, video and data signals up to 10-gigabit Ethernet in accordance with IEEE 802.3 - provides high spare capacities to the limit values.

Exceeds the requirements for Category 6A connecting components (up to 500 MHz) as defined in ISO/IEC 60603-7-51.

Applicable for Power over Ethernet (PoE) / PoE+ in accordance with IEEE 802.3at.

Compact design for easy flush or duct mounting and deployment in floor boxes.

Can be used in combination with design families from many vendors.

Housing made of zinc die casting. Cable feed from all sides (+/- 30° angle).

Combined shielding contact and strain relief. LSA connection technology for copper wires from 0.4 mm up to 0.63 mm (AWG26 - AWG22), diameters over insulation from 0.7 mm up to 1.6 mm (PE).

Convenient head on wire termination.

Color code in accordance with T568-A and T568-B.

Temperature range from - 40° C up to + 70° C.

Proprietà elettriche

EMC shielded

Standards

Cat./Class Cat.6_A / Class E_A

Versions

Numero Materiale	Product	Colore	Peso [kg]	Packing unit
435060	UP-K Data outlet CSA Plus 2/8 Cat.6 _A (IEC), with central plate	bianco puro	0,15 kg	1 pc.
435067	UP-K Data outlet CSA Plus 1/8 Cat.6 _A (IEC), with central plate	bianco puro	0,15 kg	1 pc.
417976	Central plate (50 x 50mm) for CSA Plus 2/8	ostrica bianca	0,01 kg	10 pcs.
417979	Central plate (50 x 50mm) for CSA Plus 1/8	ostrica bianca	0,01 kg	10 pcs.

Con riserva di modifiche tecniche

A partire da 2021-01-27 11:41:58