

UP/UP-K Outlet CSA Plus 2/8 (1/8)

shielded, Category 6_A
flush/duct mounted & floor boxes
with 1 or 2 RJ45 jacks Cat. 6A (IEC) shielded, angled



- 1 Data outlet CSA Plus 2/8 Cat.6A
with central plate
2 Data outlet CSA Plus 1/8 Cat.6A
with central plate

Description

Data outlet CSA Plus Cat. 6A shielded, angled, for the transmission of digital and analogue voice, video and data signals up to 10-gigabit Ethernet in accordance with IEEE 802.3 - provides high spare capacities to the limit values.
Exceeds the requirements for Category 6A connecting components (up to 500 MHz) as defined in ISO/IEC 60603-7-51.
Applicable for Power over Ethernet (PoE) / PoE+ in accordance with IEEE 802.3at.
Compact design for easy flush or duct mounting and deployment in floor boxes.
Can be used in combination with design families from many vendors.
Housing made of zinc die casting. Cable feed from all sides (+/- 30° angle).
Combined shielding contact and strain relief. LSA connection technology for copper wires from 0.4 mm up to 0.63 mm (AWG26 - AWG22), diameters over insulation from 0.7 mm up to 1.6 mm (PE).
Convenient head on wire termination.
Color code in accordance with T568-A and T568-B.
Temperature range from - 40° C up to + 70° C.

Versions

Material number	Product	Colour	Weight [kg]	Packing unit
435060	UP-K Data outlet CSA Plus 2/8 Cat.6 _A (IEC), with central plate	pure white	0.15 kg	1 pc.
435067	UP-K Data outlet CSA Plus 1/8 Cat.6 _A (IEC), with central plate	pure white	0.15 kg	1 pc.
417976	Central plate (50 x 50mm) for CSA Plus 2/8	oyster white	0.01 kg	10 pcs.
417979	Central plate (50 x 50mm) for CSA Plus 1/8	oyster white	0.01 kg	10 pcs.