

## UP-K Faceplate 2x, 3x

duct mounted & floor boxes

for 2 or 3 RJ45 modules MS-K/KS-TS, angled

GERMAN STANDARD



**1**



**2**



**3**

- 1 Faceplate for 2 modules MS-K/KS-TS 1/8, with central plate, without cover frame  
 2 Faceplate for 3 modules MS-K/KS-TS 1/8, with central plate, without cover frame

3 cover frame 1-fold for faceplates

### Description

Faceplates for the installation of 2 and 3 shielded RJ45 modules MS-K Plus 1/8 Cat.6A or KS-TS 1/8 Cat.6/EA.

Suitable for flush and duct mounting as well as for floor box systems.

In case of an installation in a flush-mount cup please use 2-port faceplates (Figure 1)!

Mounting frame made of zinc die casting (offers possibility for connection to equipotential bonding).

The snap-in modules are easily fitted into the faceplates.

Unused ports are covered with blank covers (metal) that can be removed.

The central plate has a labelling field with transparent cover.

The pure white versions are supplied with pure white dust shutters to enable the replacement of the grey shutters at the installed modules.

The mounting frames of the 2-port faceplate can be used together with all customary TAE central plates (for multiple designs).

Delivery without modules.

### Application

Suitable for the following Datwyler modules:

- RJ45 module MS-K Plus 1/8 Cat.6A shielded
- RJ45 module KS-TS 1/8 Cat.6/EA shielded

### Versions

Material number	Product	Colour	Weight [kg]
440015	UP-K Faceplate for 2x MS-K 1/8, angled, with central plate (delivery without cover frame, modules)	oyster white	0.04 kg
440027	UP-K Faceplate for 2x MS-K 1/8, angled, with central plate and 2 dust shutters (without cover frame, modules)	pure white	0.03 kg
440028	UP-K Faceplate for 3x MS-K 1/8, angled, with central plate and 3 dust shutters (without cover frame, modules)	pure white	0.04 kg