

## NAP / NUP Wall outlet IP55

surface / flush mounted in plumbed rooms

for 2 modules SWISS STANDARD



Surface mounted version, IP55



Flush mounted version, IP55

### Description

In structured premises cabling in the industrial sector, especially in high-humidity rooms, for the transmission of Ethernet protocols. Wall outlet IP 55, for high-humidity rooms, surface mounted (NAP) or flush mounted (NUP), for a maximum of 2 modules. Protection rating IP55 when closed only. Shatter-proof housing, similar to RAL 9010. Cable entry from above or from below. Delivery without modules.

### Application

Suitable for the following Datwyler modules:

- PS-GG45 7A 4P shielded
- RJ45 module KS-T 1/8 Cat. 6/EA tool-less shielded
- RJ45 module MS-C6A 1/8 Cat. 6A 180-K (Keystone), shielded

### Versions

Material number	Product	Colour	Weight [kg]	Packing unit	GTIN / EAN
30920500ZY	(CH) NUP Wall outlet IP55 for 2 modules (delivery without modules)	pure white	0.12 kg	1 pc.	40393910089059
30920400ZY	(CH) NAP Wall outlet IP55 for 2 modules (delivery without modules)	pure white	0.22 kg	1 pc.	40393910089066

Subject to technical modification

As of 2023-01-13 07:50:23