

NAP / NUP Wall outlet IP55

surface / flush mounted in plumbed rooms

for 2 modules SWISS STANDARD



Surface mounted version, IP55



Flush mounted version, IP55

Descrizione

In structured premises cabling in the industrial sector, especially in high-humidity rooms, for the transmission of Ethernet protocols. Wall outlet IP 55, for high-humidity rooms, surface mounted (NAP) or flush mounted (NUP), for a maximum of 2 modules. Protection rating IP55 when closed only. Shatter-proof housing, similar to RAL 9010. Cable entry from above or from below. Delivery without modules.

Applicazione

Suitable for the following Datwyler modules:

- PS-GG45 7A 4P shielded
- RJ45 module KS-T 1/8 Cat. 6/EA tool-less shielded
- RJ45 module MS-C6A 1/8 Cat. 6A 180-K (Keystone), shielded

Versioni

Codice art.	Prodotto	Colore	Peso [kg]	Unità di imballaggio	GTIN / EAN
30920500ZY	(CH) NUP Wall outlet IP55 for 2 modules (delivery without modules)	bianco puro	0,12 kg	1 pc.	40393910089059
30920400ZY	(CH) NAP Wall outlet IP55 for 2 modules (delivery without modules)	bianco puro	0,22 kg	1 pc.	40393910089066

Con riserva di modifiche tecniche

A partire da 2023-01-13 07:50:23