

## FO-DCS modular panels, 19"/1U

to take 3 FO-DCS plug-in modules / front plates 3U/7HP



Modularly equippable FO-DCS 19"/1U panel



Blank partial front plate

### Description

Sturdy aluminium housing with base, side panels and front 19"/1U mounting brackets.  
Pre-assembled to take a maximum of three 3U/7HP FO-DCS plug-in modules or front plates.  
3 cable support rails for the back side cable entries are enclosed separately.

### Applicazione

The modularly equippable 19"/1U panel can be used for a wide variety of applications, depending on the type of plug-in module. It can be used as a modular high-density solution for up to 36 duplex ports (72 fibres) or up to 36 MTP ports (432 fibres) in the data centre environment.

It will accept up to 3 FO-DCS 3U/7HP plug-in modules or up to 3 FO-DCS 3U/7HP front plates that are used to terminate pre-assembled LCD or MTP® trunk or breakout cables or fibre optic cables which are spliced in-situ.

Easy migration to all parallel optic applications, e.g. to 40/100 GbE, is possible with FO-DCS 3U/7HP MTP front plates.

### Proprietà generali

Acceptance capacity 3 FO-DCS inserts

### Scope of delivery

19"/1U panel with 19" mounting brackets (without plug-in modules / front plates)

3 cable support rails, enclosed separately

19" mounting material Can be combined with various blanking panels and management panels from the Datwyler range.

### Nota

MTP® is a registered brand of US Conec.

### Versions

Numero Materiale	Product	Dimensioni esterne	Colore	Peso [kg]	Packing unit
470543	FO-DCS modular panel, 19"/1U (delivery without plug-in modules/ front panels)	1 U, 44.4 mm x 482.6 mm x 315 mm	argento	1,2 kg	1 pc.
470643	FO-DCS modular panel, 19"/1U (delivery without plug-in modules/ front panels)	1 U, 44.4 mm x 482.6 mm x 315 mm	nera	2,78 kg	1 pc.

Con riserva di modifiche tecniche

A partire da 2021-02-18 13:41:33