

Server Racks Standard DSRS

19 /42U


with perforated front and rear doors



Server Rack Standard DSRS, 42U, 800 x 1000 mm

Description

The Datwyler Server Racks Standard DSRS are designed to provide good-quality cabinets that offer an unrivaled cost-performance ratio.



Top panel example [mm]

Proprietà meccaniche

allegabile	yes
Classe di protezione	IP 30
Messa a terra	pre-installed flat earthing kit
Pannelli laterali	Removable, locks with universal key
Pannello inferiore	Integrated standard steel panels with several covered 300 x 100 mm holes and 500 x 115 mm holes (one 300 x 115 mm + two 100 x 115 mm)
Pannello superiore	Integrated standard steel panels with several covered 300 x 100 mm holes and 500 x 115 mm holes (one 300 x 115 mm + two 100 x 115 mm). Ventilation: Via a covered 420 x 440 mm hole.
Piedi	Set of adjustable feet as standard
Porta d'ingresso	One-piece perforated doors, 86% perforation, with swivel handle lock, 1-point locking, DIN single-profile cylinder, universal key, up to 180° aperture angle; front door can be hinged right or left (easy to change)
Porta posteriore	One-piece perforated doors, 86% perforation, with swivel handle lock, 1-point locking, DIN single-profile cylinder, universal key, up to 180° aperture angle.
Profilo di montaggio	2 pairs of 19" vertical profiles (front / rear), stepless depth adjustment from inside, with U label; rack offers 3 vertical 19"/2U positions per 19" extrusion
Telaio di base	Welded sheet steel frame (1.5 mm)

Scope of delivery

Comes with 28 mounting kits (screws, cage nuts, washers).

- plinth, 100 mm (4 corners, 4 panels and mounting kit)
- cable entry, double brush strip panel with 300 x 100 opening
- potential equalization bar 8 x 8 mm, 22 connection points, 40A, with mounting kit and earthing cable
- cable mangement / cable tray, 1800 mm height

Nota

More dimensions available on request

Versions

Numero Materiale	Product	Dimensioni esterne	Colore	Peso [kg]	Packing unit	Carico massimo [KG]
195305	Server Rack Standard DSRS, 42 U, 1.987 x 800 x 1.000 mm	42 U, 1987 mm x 800 mm x 1000 mm	nera	133 kg	1 pc.	1.000
195306	Server Rack Standard DSRS, 42 U, 1.987 x 800 x 1.200 mm	42 U, 1987 mm x 800 mm x 1200 mm	nera	158 kg	1 pc.	1.000

Con riserva di modifiche tecniche

A partire da 2021-01-27 11:42:02