

Server Racks Standard DSRS

19 /42U

with perforated front and rear doors




Server Rack Standard DSRS, 42U, 800 x 1000 mm

Description

The Datwyler Server Racks Standard DSRS are designed to provide good-quality cabinets that offer an unrivaled cost-performance ratio.

Top panel example [mm]



Mechanical properties

| | |
|------------------|---|
| Base frame | Welded sheet steel frame (1.5 mm) |
| Bayable | yes |
| Bottom Panel | Integrated standard steel panels with several covered 300 x 100 mm holes and 500 x 115 mm holes (one 300 x 115 mm + two 100 x 115 mm) |
| Earthing | pre-installed flat earthing kit |
| Feet | Set of adjustable feet as standard |
| Front door | One-piece perforated doors, 86% perforation, with swivel handle lock, 1-point locking, DIN single-profile cylinder, universal key, up to 180° aperture angle; front door can be hinged right or left (easy to change) |
| Mounting profile | 2 pairs of 19" vertical profiles (front / rear), stepless depth adjustment from inside, with U label; rack offers 3 vertical 19"/2U positions per 19" extrusion |
| Protection class | IP 30 |
| Rear door | One-piece perforated doors, 86% perforation, with swivel handle lock, 1-point locking, DIN single-profile cylinder, universal key, up to 180° aperture angle. |
| Side panels | Removable, locks with universal key |
| Top Panel | Integrated standard steel panels with several covered 300 x 100 mm holes and 500 x 115 mm holes (one 300 x 115 mm + two 100 x 115 mm). Ventilation: Via a covered 420 x 440 mm hole. |

Scope of delivery

Comes with 28 mounting kits (screws, cage nuts, washers).

- plinth, 100 mm (4 corners, 4 panels and mounting kit)
- cable entry, double brush strip panel with 300 x 100 opening
- potential equalization bar 8 x 8 mm, 22 connection points, 40A, with mounting kit and earthing cable
- cable mangement / cable tray, 1800 mm height

Note

More dimensions available on request

Versions

| Material number | Product | Outer dimensions | Colour | Weight [kg] | Packing unit | Maximum Load [KG] |
|-----------------|---|--------------------------------|--------|-------------|--------------|-------------------|
| 195305 | Server Rack Standard DSRS, 42 U, 1,987 x 800 x 1,000 mm | 42 U1987 mm x 800 mm x 1000 mm | black | 133 kg | 1 pc. | 1,000 |
| 195306 | Server Rack Standard DSRS, 42 U, 1,987 x 800 x 1,200 mm | 42 U1987 mm x 800 mm x 1200 mm | black | 158 kg | 1 pc. | 1,000 |