

HDPS MTP cassettes, 1x MTP to 6x LCD .

for HDPS modular panel

for OM3, OM4, OS2



High-performance pre-terminated HDPS MTP cassettes, 12F

Description

Polycarbonate (PC) housing with aluminium cover.

At the rear each HDPS cassette has 1 MTP coupler which is routed to the front couplers (6x LC duplex) by way of an internal fanout and integrated fibre management.

Can be easily inserted into one of the panel's sliding support frames. The sliding hardware with guide handle (at the rear of the cassette) allow for easy installation and maintenance.

Applicazione

HDPS MTP® cassettes are suitable for all high-performance applications with duplex signals particularly in the data centre environment. They support modular application in the HDPS modular panel (19"/1U).

They are used to accept pre-assembled MTP trunk cables - for quick and simple installations.

Packing densities of up to 144 fibres on 1U are achieved with these cassettes.

They are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

Proprietà generali

Acceptance capacity	6 duplex ports (12 fibres)
Fully equipped	Yes

Scope of delivery

Housing with front panel, equipped with 6 LC duplex adapters (ceramic sleeves).

Rear fitted with 1 MTP adapter (Type A).

1 module fanout (High P): per 12 fibres, 1x MTP Elite® (female) to 12x LC (ceramic ferrules).

Delivery inclusive of test reports for fanout.

Nota

MTP® and MTP Elite® are registered brands of US Conec.

Versions

Numero Materiale	Product	Dimensioni esterne	Colore	Peso [kg]	Packing unit
240695	HDPS MTP cassette, 12F, 1x MTP to 6x LCD /PC, OM3	12 mm x 91 mm x 163 mm	nera	0,01 kg	1 pc.
240696	HDPS MTP cassette, 12F, 1x MTP to 6x LCD /PC, OM4	12 mm x 91 mm x 163 mm	nera	0,01 kg	1 pc.
240693	HDPS MTP cassette, 12F, 1x MTP to 6x LCD /PC, OS2 (G.652.D)	12 mm x 91 mm x 163 mm	nera	0,01 kg	1 pc.
240694	HDPS MTP cassette, 12F, 1x MTP to 6x LCD /APC, OS2 (G.652.D)	12 mm x 91 mm x 163 mm	nera	0,01 kg	1 pc.

