

Preassembled cables. MTP - MTP, G50/125 OM3



image similar

Description

Compact, metal-free cable construction with FR/LSOH cable sheath and 12 to 144 fibres. The length of individual cables ("legs") may be defined on the basis of a specific project. All individual cables are assembled using MTP connectors with high-performance 12-fibre Elite® ferrules (LCD connectors available on request). Polarisation modes can be type A, type B or type C. The preassembled cables guarantee high reliability based on 100% performance test and quality inspection in the factory. The cables come with an effective protection for cable and connector. Quick and easy installation on site. Rodent protection optional.

Application

Campus and inter-building backbone cabling
 Industrial plant cabling
 Fiber optic cabling in data centers

Construction

Couleur de la gaine	aqua
Gaine extérieure	LSZH

Propriétés optiques

Atténuation de réflexion RL minimal connecteur A	55 dB
Atténuation de réflexion RL minimal connecteur B	55 dB
Ferrule polissage connecteur A	Elite PC 0°
Ferrule polissage connecteur B	Elite PC 0°
Perte d'insertion IL maximal connecteur A	0,3 dB
Perte d'insertion IL maximal connecteur B	0,3 dB
Type de fibre	G50/125 OM3

Scope of delivery

Preassembled cable, packed in recyclable cardboard drum or box
Installation guide enclosed
Comes with test protocol

Normes

Zéro halogène, pas de gaz corrosifs	IEC 60754-1/-2
Propagation de la flamme	IEC 60332-3-24
Densité De Fumée	IEC 61034-1/-2

Remarque

MTP® and MTP Elite® are registered brands of US Conec.

Versions

Numéro de matériau	Produit	Couleur de la gaine	Longueur (m)	Poids [kg]
4122418	Preassembled cables MTP - MTP	aqua	1	0,01 kg
4122437	Preassembled cables MTP - MTP	aqua	1	0,01 kg
4122443	Preassembled cables MTP - MTP	aqua	1	0,01 kg
4122419	Preassembled cables MTP - MTP	aqua	1	0,01 kg
4122438	Preassembled cables MTP - MTP	aqua	1	0,01 kg
4122444	Preassembled cables MTP - MTP	aqua	1	0,01 kg

Other lengths and versions on request.