

## Preassembled cables. MTP - MTP, G50/125 OM3



image similar

### Description

Compact, metal-free cable construction with FR/LSOH cable sheath and 12 to 144 fibres. The length of individual cables ("legs") may be defined on the basis of a specific project. All individual cables are assembled using MTP connectors with high-performance 12-fibre Elite® ferrules (LCD connectors available on request).  
Polarisation modes can be type A, type B or type C.  
The preassembled cables guarantee high reliability based on 100% performance test and quality inspection in the factory. The cables come with an effective protection for cable and connector.  
Quick and easy installation on site.  
Rodent protection optional.

### Application

Campus and backbone cabling  
Industrial plant cabling  
Fibre optic cabling in data centres

### Construction

Outer sheath colour	aqua
Outer sheath material	LSZH

### Optical Properties

Ferrule polishing connector A	Elite PC 0°
Ferrule polishing connector B	Elite PC 0°
Fibre type	G50/125 OM3
IL maximal, connector A	0.3 dB
IL maximal, connector B	0.3 dB
RL minimal, connector A	55 dB
RL minimal, connector B	55 dB

### Scope of delivery

Preassembled cable, packed in recyclable cardboard drum or box  
Installation guide enclosed  
Comes with test protocol

### Standards

Zero halogen no corrosive gases	IEC 60754-1/-2
Flame Spread	IEC 60332-3-24
Smoke Density	IEC 61034-1/-2

### Note

MTP® and MTP Elite® are registered brands of US Conec.

## Versions

Material number	Product	Outer sheath colour	Length (m)	Weight [kg]
4122418	Preassembled cables MTP - MTP	aqua	1	0.01 kg
4122437	Preassembled cables MTP - MTP	aqua	1	0.01 kg
4122443	Preassembled cables MTP - MTP	aqua	1	0.01 kg
4122419	Preassembled cables MTP - MTP	aqua	1	0.01 kg
4122438	Preassembled cables MTP - MTP	aqua	1	0.01 kg
4122444	Preassembled cables MTP - MTP	aqua	1	0.01 kg

Other lengths and versions on request.

Subject to technical modification

As of 2020-10-28 12:09:33