Patch cord. MTP Elite - MTP Elite, G50/125 OM3

Description

Round, very flexible FO patch cables, assembled with high-performance MTP Elite®, connectors at both ends.
The round patch cords are pre-assembled with high-performance MTP connectors at both ends.
Compact, space saving cable design with Ø 3.0 mm (cable sheath).
Bend insensitive fibre, suitable for small space application.
Labelling at both cable ends for quick identification.

Impresión de aplicaciones

OM3 MTP-on-MTP patch cords are suitable for all high performance applications with parallel optical signals in the data centre environment.
nur China

Construcción

Color de la funda exterior	aqua
Material exterior de la vaina	FR/LSZH

Propedades ópticas

Conector de pulido de férulas A	Elite PC 0°
Conector de pulido de férulas B	Elite PC 0°
IL máximo, conector A	0,3 dB
IL máximo, conector B	0,3 dB
IL típico, conector A	0,15 dB
IL típico, conector B	0,15 dB
RL minimal, conector A	30 dB
RL minimal, conector B	30 dB
RL típico, conector A	35 dB
RL típico, conector B	35 dB
Tipo de fibra	G50/125 OM3

Forma de suministro

Supplied with test report

Estándares

MTP standard (IEC)	IEC 61754-7, IEC 61755-3-31, IEC 61755-3-32
Norma de polaridad	TIA-568-C.3 Type A,B,C
Cero halógeno gases no corrosivos	IEC 60754-1/-2
Dispersión de llamas	IEC 60332-3
Densidad de humo	IEC 61034-1/-2

Nota

MTP and MTP Elite are registered brands of US Conec.

Versions

Número de material	Producto	Color de la funda exterior	Longitud (m)	Peso [kg]
4135014	Patch cord MTP Elite - MTP Elite	aqua	1	0,04 kg
4135028	Patch cord MTP Elite - MTP Elite	aqua	1	0,01 kg
4135015	Patch cord MTP Elite - MTP Elite	aqua	2	0,05 kg
4135029	Patch cord MTP Elite - MTP Elite	aqua	2	0,01 kg
4135016	Patch cord MTP Elite - MTP Elite	aqua	3	0,05 kg
4135030	Patch cord MTP Elite - MTP Elite	aqua	3	0,01 kg
4135017	Patch cord MTP Elite - MTP Elite	aqua	4	0,06 kg
4135031	Patch cord MTP Elite - MTP Elite	aqua	4	0,01 kg
4135018	Patch cord MTP Elite - MTP Elite	aqua	5	0,07 kg
4135032	Patch cord MTP Elite - MTP Elite	aqua	5	0,01 kg

Push-pull tabs are optionally available for easy patching in high-density application. Other lengths and versions on request.